



RECOMMENDED PCB PATTERN DIM.
TOLERANCE : ±0.05

| HIGH | SOCKET(H1) |
|------|------------|
| 1.50 | 1.35 |
| 2.00 | 1.85 |
| 2.50 | 2.35 |

| MATED HEIGHT | |
|---------------|-------------|
| Female Height | Male Height |
| A:1.5 | 1.5 |
| B:2.0 | 1.5 |
| C:2.5 | 1.5 |

| MATED HEIGHT |
|----------------------|
| X0511FVS-XXXXS-LPV01 |
| Single high |
| X0511FVS-XXXXS-LPV01 |

Specifications:

- Voltage rating:50V AC/DC
- 50V AC/DC
- Current rating:0.5A AC/DC
- 0.5A AC/DC
- Withstanding voltage:1500V AC/minute
- 1500V AC/
- Temperature range:-25 ~+85
- 25 ~+85
- Insulation resistance:≥1000MΩ
- ≥1000MΩ
- Contact resistance:≤55mΩ
- ≤20mΩ
- After environmental testing:≤40mΩ
- ≤40

X0511 F V S-XX X X S- LP V01

- Series No
- Category:F-Female
- Welding Board Angle:V-Straight 180°
- Welding Way:S-SMT
- Row No-Pin No:XXP
- Female Height:A:1.5mm;B:2.0mm;C:2.5mm
- Male Height:D:0.5mm;
- special No:S-With positioning Column
- Material:LP-LCP
- Metal plating:Gold Flash

| P数 | 尺寸 | | | P数 | 尺寸 | | |
|----|-------|-------|-------|----|-------|-------|-------|
| | A | B | C | | A | B | C |
| 10 | 5.60 | 3.50 | 2.00 | 32 | 16.60 | 14.50 | 13.00 |
| 12 | 6.10 | 4.00 | 2.50 | 34 | 17.10 | 15.00 | 13.50 |
| 14 | 6.60 | 4.50 | 3.00 | 36 | 17.60 | 15.50 | 14.00 |
| 16 | 7.10 | 5.00 | 3.50 | 38 | 18.10 | 16.00 | 14.50 |
| 18 | 7.60 | 5.50 | 4.00 | 40 | 18.60 | 16.50 | 15.00 |
| 20 | 8.10 | 6.00 | 4.50 | 42 | 19.10 | 17.00 | 15.50 |
| 22 | 8.60 | 6.50 | 5.00 | 44 | 19.60 | 17.50 | 16.00 |
| 24 | 9.10 | 7.00 | 5.50 | 46 | 20.10 | 18.00 | 16.50 |
| 26 | 9.60 | 7.50 | 6.00 | 48 | 20.60 | 18.50 | 17.00 |
| 28 | 10.10 | 8.00 | 6.50 | 50 | 21.10 | 19.00 | 17.50 |
| 30 | 10.60 | 8.50 | 7.00 | 52 | 21.60 | 19.50 | 18.00 |
| 32 | 11.10 | 9.00 | 7.50 | 60 | 22.10 | 20.00 | 18.50 |
| 34 | 11.60 | 9.50 | 8.00 | 70 | 22.60 | 20.50 | 19.00 |
| 36 | 12.10 | 10.00 | 8.50 | 80 | 23.10 | 21.00 | 19.50 |
| 38 | 12.60 | 10.50 | 9.00 | | | | |
| 40 | 13.10 | 11.00 | 9.50 | | | | |
| 42 | 13.60 | 11.50 | 10.00 | | | | |
| 44 | 14.10 | 12.00 | 10.50 | | | | |
| 46 | 14.60 | 12.50 | 11.00 | | | | |
| 48 | 15.10 | 13.00 | 11.50 | | | | |
| 50 | 15.60 | 13.50 | 12.00 | | | | |
| 52 | 16.10 | 14.00 | 12.50 | | | | |

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|---|-------------|------|---------|----------|------------------------|
| ΔX | | | | | ANGLAR ±5° |
| ΔX | | | | | L≤ 4 ±0.2 |
| ΔX | | | | | 4<L≤ 16 ±0.3 |
| | | | | | 16<L≤ 63 ±0.4 |
| | | | | | L> 63 ±0.5 |
| REVISIONS | | | | | UNSPECIFIED TOLERANCES |
| www.helloxkb.com www.helloxkb.cn www.xk-dg.cn | | | | | |



| DSND | SCALE: N/A | MODEL TYPE: |
|------|-------------|-----------------------------------|
| DWN | VIEW: | PART NO.: 0.50mm Style Connectors |
| CHKD | UNIT: mm/in | DWG NO.: X0511FVS-XXXXS-LPV01 |
| APPD | SIZE: A4 | WEIGHT SHEET REVISION |
| | | 1/1 A0 |

XKB INDUSTRIAL PRECISION CO., LIMITED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [93696-330](#) [224393](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [2-22603-0](#) [MDF7-40DP-2.54DSA\(55\)](#) [5031084030](#) [MIT-114-03-F-D-K](#) [55323-1519](#) [45970-4130](#) [YFT-20-05-H-03-SB-K](#) [503308-3040](#) [026-6203-PDB](#) [027-6203-PDB](#) [069159702701000](#) [101A10019X](#) [105061100000861+](#) [55650-0588-C](#) [75140-7012](#) [87471-650](#) [YTW-30-07-H-Q-410-140](#) [YTT-112-01-H-Q](#) [063209](#) [0717420006](#) [FCN-268F024-G0D](#) [10124054-515LF](#) [68685-603](#) [8-1616154-3](#) [MIS-019-01-F-D](#) [IL-WX-10PB-HF-B-E1000E](#) [YFT-50-05-H-10-SB-K](#) [FCN-268M024-G/3D](#) [MDF7-16DP-2.54DSA\(55\)](#) [AXE810124](#) [FCN-214J100-G/0](#) [FCN-230C068-E/S](#) [AXE812124](#) [74220-001](#) [354184](#) [P50-028-DDS-TG](#) [53309-2471](#)