



RECOMMENDED PCB PATTERN DIM

Specifications:

规格:

Voltage rating:50V AC/DC

额定电压: 50V AC/DC

Current rating:0.5A AC/DC

额定电流: 0.5A AC/DC

Withstanding voltage:200V AC/minute

耐受电压: 200V AC/分钟

Temperature range:-25°C~+85°C

温度范围: -25°C~+85°C

Insulation resistance :500MΩ min

绝缘电阻: 500MΩ Min

Contact resistance:40mΩ Max

接触电阻: 40mΩ Max

X0511 F V S-XX X X -LP V01  
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- 1.Series No
- 2.Category:F-Female
- 3.Welding Board Angle:V-Straight 180°
- 4.Welading Way:S-SMT
- 5.Row No.Pin No:XX-10-80P
- 6.Height:A=1.5mm ; B=2.0mm; C=2.5mm
- 7.Special No:Blank-Without positioning Columnm  
S-With positioning Columnm
- 8.Material:LP-LCP UL 94V-0
- 9.Plating:V01-Gold Flash

HIGH	SOCKET(H1)
1.50	1.35
2.00	1.85
2.50	2.35

Poles	Dimensions(mm)				Poles	Dimensions(mm)			
	A	B	C	D		A	B	C	D
10	5.60	3.50	2.00	3.90	46	14.60	12.50	11.00	12.90
12	6.10	4.00	2.50	4.40	48	15.10	13.00	11.50	13.40
14	6.60	4.50	3.00	4.90	50	15.60	13.50	12.00	13.90
16	7.10	5.00	3.50	5.40	52	16.10	14.00	12.50	14.40
18	7.60	5.50	4.00	5.90	54	16.60	14.50	13.00	14.90
20	8.10	6.00	4.50	6.40	56	17.10	15.00	13.50	15.40
22	8.60	6.50	5.00	6.90	58	17.60	15.50	14.00	15.90
24	9.10	7.00	5.50	7.40	60	18.10	16.00	14.50	16.40
26	9.60	7.50	6.00	7.90	62	18.60	16.50	15.00	16.90
28	10.10	8.00	6.50	8.40	64	19.10	17.00	15.50	17.40
30	10.60	8.50	7.00	8.90	66	19.60	17.50	16.00	17.90
32	11.10	9.00	7.50	9.40	68	20.10	18.00	16.50	18.40
34	11.60	9.50	8.00	9.90	70	20.60	18.50	17.00	18.90
36	12.10	10.00	8.50	10.40	72	21.10	19.00	17.50	19.40
38	12.60	10.50	9.00	10.90	74	21.60	19.50	18.00	19.90
40	13.10	11.00	9.50	11.40	76	22.10	20.00	18.50	20.40
42	13.60	11.50	10.00	11.90	78	22.60	20.50	19.00	20.90
44	14.10	12.00	10.50	12.40	80	23.10	21.00	19.50	21.40

X0511FVS-XXXX-LPV01	LCP	Phosphor Bronze	X0511W
PART NO	Material	Material(Pin)	Suitable XKB Wafer

DSND	SCALE: N/A	MODEL TYPE:
DWN	VIEW:	0.5mm BTB Style Connector
CHKD	UNIT: mm/in	PART NO.:
APPD	SIZE: A4	X0511FVS-XXXX-LPV01
		DWG NO.:
		X-X0511FVS-XXXX-LPV01
		WEIGHT
		SHEET
		REVISION
		1/1
		A0



XKB INDUSTRIAL PRECISION CO.,LIMITED

					ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
MARK					L > 63	±0.5
	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	
	REVISIONS					

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [MIS-048-01-F-D-DP-K](#)  
[832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [93696-330](#) [224393](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [MDF7-40DP-2.54DSA\(55\)](#)  
[55323-1519](#) [069159702701000](#) [101A10019X](#) [105061100000861+](#) [75140-7012](#) [87471-650](#) [1744382-4](#) [063209](#) [10124054-515LF](#) [68685-603](#)  
[8-1616154-3](#) [541371078](#) [IL-WX-10PB-HF-B-E1000E](#) [FX23-40P-0.5SV15B](#) [FCN-214J100-G/0](#) [354184](#) [P50-028-DDS-TG](#) [53309-2471](#)  
[54546-2071](#) [1586617-1](#) [504248-1210](#) [504248-2010](#) [1-1437355-2](#) [9159005551906](#) [NDS100-004-BF](#) [93696-730LF](#) [91922-31141LF](#) [505274-](#)  
[3440](#) [501493-2410](#) [504208-3410](#) [505006-0811](#) [505274-2040](#) [202436-1600](#) [202477-0414](#) [71660-7580](#) [73420-5192](#) [360-10-107-00-001000](#)