



APPLICABLE WIRE : AWG#34,AWG#36



MATED CONDITION



Specifications:

规格:
Voltage rating:30V AC/DC
 额定电压: 30V AC/DC
Current rating: 0.2A AC/DC(AWG#36)
 0.3A AC/DC(AWG#34)
 额定电流: 0.2A AC/DC(AWG#36)
 0.3A AC/DC(AWG#34)
Withstanding voltage:200V AC/minute
 耐压电压: 200V AC/分钟
Temperature range:-25℃ ~ +85℃
 温度范围: -25℃ ~ +85℃
Insulation resistance:≥100MΩ
 绝缘电阻: ≥100MΩ
Contact resistance: ≤30mΩ
 接触电阻: ≤30mΩ
 After environment testing: ≤40mΩ
 环境试验后: ≤40mΩ
Insulation O.D.: 0.29±0.02mm(AWG#36)
 0.32±0.02mm(AWG#34)
 绝缘材料: 0.29±0.02mm(AWG#36)
 0.32±0.02mm(AWG#34)

X0600HI-L-XX-X-LP-HF

① ②③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: H-HSG
- ③ Welding Board Angle: I-HSG-hardware
- ④ Row No.-Pin No.: XX-Single row
- ⑤ Plating sytle: G-Gold plated
- ⑥ Material: LP-LCP 94V-0
- ⑦ HF-Halogen Free

Poles	Dimensions(mm)			
	A	B	C	D
2	1.36	1.80	0.60	1.65
4	2.56	3.00	1.80	2.85
5	3.16	3.60	2.40	3.45
6	3.76	4.20	3.00	4.05
8	4.96	5.40	4.20	5.25
10	6.16	6.60	5.40	6.45
12	7.36	7.80	6.60	7.65
16	9.76	10.20	9.00	10.05

PART NO	Material	Wire Range	Insulation	Material(Terminal)	Finish(Terminal)	Suitable XKB Terminal
X0600HI-XXG-LPHF	LCP UL94V-0 Halogen Free(Black)	AWG#36/AWG#34	0.32Max	Phosphor Bronze	Gold-Flash	X0600W

广东星坤科技股份有限公司

生 日期
 日期
 文件工程章
 REVISIONS
 DATE REVISED APPROVED
 UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.: 0.60mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Connectors](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[571763P](#) [59811-0000](#) [61-168618-12P](#) [D20419-211](#) [76871-1403](#) [PCR-E36PM](#) [PCS-XE26LKA](#) [PCS-XES68MS+](#) [G38A71314B](#) [DX40-50P\(55\)](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [192991-0703](#) [91-569786-35H](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-261Z008](#) [2000314-1](#) [200331-1](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#) [PCS-XE26SLFDT+](#) [G730VID08BDC24](#) [HDMR-29-01-S-SM-TR](#) [HDR-E14MSG1+](#) [54182-0605](#) [UE86K842720321](#) [38113800006](#) [DP3AR020WQ1R200](#) [DRA-26PC-F0R](#) [Z4.102.0680.0](#) [500-1040](#) [500-1052](#) [ZP-4008-66L](#) [10-565995-597N](#) [10-584459-12P](#) [DX40-20P\(55\)](#) [5554841-1](#) [SM3100F14S-12P](#) [SM3106F14S-7S-LC](#) [SM3106R18-18S](#) [U90B3054061110](#) [U65-E04-4020](#) [557-262M2-06C](#) [PCS-96LFD+](#) [60-042222-02S](#) [10099439-003C-TRLF](#) [226-0348-000](#) [10137239-0021LF](#)