Autodesk

2.84±0.15 [0.112]	A±0.40 B±0.30 0±0.25 2.77±0.15 [0.109] 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	17.15 [0.675] 5.85 [0.231]		C±0.30		0.90 [0.036]	Specifications: 规格: 1.Voltage rating:250VAC/DC 额定电压: 250V AC/DC 2.Current rating:1A AC/DC 3.Withstanding voltage:500V AC/minute 耐受电压: ≥500V AC/分钟 4.Temperature range:-40°C-+105°C 温度范围: -40°C-+105°C 5.Insulation resistance:1000MΩMIN 绝缘电阻: ≥1000MΩ 6.Contact resistance:20mΩMax					
							7	胶芯: PBT (8.The iron she Plating 铁壳: SPCC B、成品不能 X08 XX F	core:PBT UL94V-0 BT UL94V-0 shell:SPCC Nivkel Plating/Tin PCC,镀镍/镀锡 能有弯针,R角不一致等不良。			
							Image: Constraint of the state of					
Δx Δx Δx MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR $\pm 5^{\circ}$ L≤ 4 ± 0.2 4 <l≤ 16<="" td=""> ± 0.3 16<l≤ 63<="" td=""> ± 0.4 L> 63 ± 0.5</l≤></l≤>	XKB	DSND DWN CHKD APPD	VIE		PART NO.	D-U : X08)	JSB XXFXXX1 XXFXXX1
REVISIONS UNSPECIFIED TOLERANCES XKB INDUSTRIAL PRECISION CO.,LIMITED WEIGHT SHEET R www.helloxkb.com www.helloxkb.com www.kelloxkb.com www.kelloxkb.com 1/1												T REVISION A0

Autodesk

Autodesk

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by XKB manufacturer:

Other Similar products are found below :

30-1231 30-528 30-504 30-519 33DVIR-24S1B 47648-2000 2002-400 TC142X 769-103/021-000 1932649-1 CP30200GM3 67881 HAFBF HBLBH HBLBI HAFBG HAFBH HAGBF HAGBG HAGBI HAGBJ HBLBJ AABIE AABIF AABIG AABIH AABII AABII AABIK AABIL AACBE AACBF AACBG ABIBF ABIBG ABIBH 42154 AACBH AACBI AACBJ AACBK AACBL AAIBD AAIBF AAIBH AAIBI AANBF AANBG AANBH AANBI