Autodesk

Autodesk				
Autodesk	2.84±0.35 [0.112]	A±0.40 B±0.30 D±0.65 2.77±0.35 [0.109] C±0.25		Specifications: 规格: 1.Voltage rating:250VAC/DC 额定电压: 250V AC/DC 2.Current rating:1A AC/DC 额定电流: 1A AC/DC 3.Withstanding voltage:500V AC/minute 耐受电压: ≥500V AC/分钟 4.Temperature range:-40°C-+105°C 温度范围: -40°C-+105°C 5.Insulation resistance:1000MΩMIN 绝缘电阻: ≥1000MΩ 6.Contact resistance:20mΩMax 接触电阻: ≥20mΩ Materiai: 材料: 7.Rubber core:PBT UL94V-0 胶芯: PBT UL94V-0
				 8.The iron shell:SPCC Nivkel Plating/Tin Plating 供売: SPCC,镀镍/镀锡 B、成品不能有弯针,R角不一致等不良。 X08 XX W X X A 3 ② ③ ④ ⑤ ⑥ ⑦ ① Series N0. ② Row No.Pin No.XX-09;15;25;37 ③ Welding Board Angle :W-Male ④ T: Tradutional C: Car-pin ⑤ Planting Categotry: 1:1U 2:2U 3:3U 4:4U 5:5U 6:6U 7:AuSn ⑥ Color:B-BLACK W-White BL-Blue ⑦ 1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 4:TYPE-4; 5:TYPE-5
				MBER OF SITIONS DIMENSION 9 30.80 25.00 16.35 11.08 10.16 15 39.14 33.30 24.75 19.39 17.78 25 53.05 47.04 38.35 33.24 30.38 37 69.32 63.50 54.75 49.86 45.72 SCALE: N/A MODEL TYPE: D-USB
-	ΔX ΔX ΔX MARK	DESCRIPTION	ANGLAR ±5° DWN L≤ 4 ±0.2 4 <l≤ 16<="" td=""> ±0.3 16<<l≤ 63<="" td=""> ±0.4 DATE REVISED APPROVED L> 63 ±0.5</l≤></l≤>	UNIT: mm/in PART NO.: UNIT: mm/in X08XXWXXX3 SIZE: A4 X-X08XXWXXX3
		REVISIONS www.helloxkb.com www.helloxkb.cn www.		SION CO.,LIMITED WEIGHT SHEET REVISION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by XKB manufacturer:

Other Similar products are found below :

30-1231 30-528 30-504 30-519 33DVIR-24S1B 47648-2000 2002-400 TC142X 769-103/021-000 1932649-1 CP30200GM3 67881 HAFBF HBLBH HBLBI HAFBG HAFBH HAGBF HAGBG HAGBI HAGBJ HBLBJ AABIE AABIF AABIG AABIH AABII AABIJ AABIK AABIL AACBE AACBF AACBG ABIBF ABIBG ABIBH 42154 AACBH AACBI AACBJ AACBK AACBL AAIBD AAIBF AAIBH AAIBI AANBF AANBG AANBH AANBI