



■ Specifications :

- Voltage rating: 50 V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤20mΩ
- After environmental testing: ≤40mΩ

X1002 H-XX E-XX HF

- ① Series No.
- ② Category : H-HSG
- ③ Row No. Pin No. XX-02P-20P
- ④ Special No: E-Have ears
- ⑤ Material: PT-PBT; N0-PA66 94V-0
- ⑥ HF-Halogen Free

| Poles | Dimensions(mm) | | | Poles | Dimensions(mm) | | |
|-------|----------------|-------|-------|-------|----------------|-------|-------|
| | A | B | C | | A | B | C |
| 02 | 1.00 | 5.00 | 2.40 | 13 | 12.00 | 16.00 | 13.40 |
| 03 | 2.00 | 6.00 | 3.40 | 14 | 13.00 | 17.00 | 14.40 |
| 04 | 3.00 | 7.00 | 4.40 | 15 | 14.00 | 18.00 | 15.40 |
| 05 | 4.00 | 8.00 | 5.40 | 16 | 15.00 | 19.00 | 16.40 |
| 06 | 5.00 | 9.00 | 6.40 | 17 | 16.00 | 20.00 | 17.40 |
| 07 | 6.00 | 10.00 | 7.40 | 18 | 17.00 | 21.00 | 18.40 |
| 08 | 7.00 | 11.00 | 8.40 | 19 | 18.00 | 22.00 | 19.40 |
| 09 | 8.00 | 12.00 | 9.40 | 20 | 19.00 | 23.00 | 20.40 |
| 10 | 9.00 | 13.00 | 10.40 | 22 | 21.00 | 25.00 | 22.40 |
| 11 | 10.00 | 14.00 | 11.40 | 24 | 23.00 | 27.00 | 24.40 |
| 12 | 11.00 | 15.00 | 12.40 | | | | |

| PART NO | Material | Suitable XKB Terminal | Suitable XKB Terminal |
|-----------------|----------------------------|-----------------------|-----------------------|
| X1002H-XXE-V0HF | PA66 UL 94V-0 Halogen Free | X1002T | X1002W |
| X1002H-XXE-N0 | PA66 UL 94V-0 | | |
| X1002H-XXE-PT | PBT UL 94V-0 | | |

广东星坤科技股份有限公司

生效

| MARK | DESCRIPTION | DATE | REVISED | APPROVED |
|------|-------------|------|---------|----------|
| ΔX | | | | |
| ΔX | | | | |
| ΔX | | | | |

日期

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

| ANGLAR | ±5° |
|-------------|------|
| L ≤ 4 | ±0.2 |
| 4 < L ≤ 16 | ±0.3 |
| 16 < L ≤ 63 | ±0.4 |
| L > 63 | ±0.5 |

UNSPECIFIED TOLERANCES

| DSND | DATE | SCALE: N/A | MODEL TYPE: |
|---------------------------------------|------|-------------|--|
| DWN | DATE | VIEW: | X1002H-XXE-N0HF |
| CHKD | DATE | UNIT: mm/in | PART NO.: 1.0mm Crimp Style Connectors |
| APPD | DATE | SIZE: A4 | DWG NO.: |
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT: 1.0g |
| | | | SHEET: 1/1 |
| | | | REVISION: A0 |

文件工程章

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)