



Specifications:

规格:

Voltage rating:50V AC/DC

额定电压: 50V AC/DC

Current rating:0.8A AC/DC

额定电流: 0.8A AC/DC

Withstanding voltage:250V AC/minute

耐受电压: 250V AC/分钟

Temperature range:-25℃-+85℃

温度范围: -25℃-+85℃

X1004 W V S -2xXX -9T V01
① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category:W-WAFER
- ③ Wedding Board Angle:V-Stringht 180°
- ④ Welding way :S-SMT
- ⑤ Row No.Pin No.: 2xXX
- ⑥ Material:9T-PA9T 94V-0
- ⑦ Plating Category:V01-Gold Flash

PIN	DIM A	DIM B	DIM C	DIM D
2X10P	9.00	12.30	10.45	11.25
2X15P	14.00	17.30	15.45	16.25
2X20P	19.00	22.30	20.45	21.25
2X25P	24.00	27.30	25.45	26.25

							DSND		DATE		SCALE: N/A	MODEL TYPE: 1.0 mm Crimp Style Connector			
				XKB	ANGLAR	±5°	DWN		DATE		VIEW:	PART NO.: X1004WVS-2xXX-9TV01			
ΔX					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm/in	DWG NO: X-X1004WVS-2xXX-9TV01			
ΔX					4 < L ≤ 16	±0.3	APPD		DATE		SIZE: A4				
ΔX					16 < L ≤ 63	±0.4									
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5						WEIGHT 1.0g	SHEET 1/1	REVISION A0	
REVISIONS							UNSPECIFIED TOLERANCES						XKB INDUSTRIAL PRECISION CO., LIMITED		
www.helloxkb.com															

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#)
[FCN-367T-T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-41-018-10-001000](#)