


- 规格 Specifications:**
- 额定电压 Voltage rating: 250VAC/DC。
  - 额定电流 Current rating: 1A AC/DC
  - 耐电压 Withstanding voltage: 300V AC/minute
  - 温度区间 Temperature range: -40°C to +105°C
  - 绝缘电阻 Insulation resistance: ≥ 500MΩ Min
  - 接触电阻 Contact resistance: ≤ 20MΩ Max
  - 材料 Material: PA6T 94V-0
  - 镀层 Plating Category: 1U"Gold
  - 波峰焊温度 Wave soldering temperature: 255±5°C, 10s

**X1311 F R-XX - C43 D24**  
 01 02 03 04 05 06

- 01 Series No.
- 02 Category: F-Female
- 03 Welding Board Angle: R-Straight 90°
- 04 Row No -Pin No: XX-01P-40P
- 05 Plastic height: C=4.3mm
- 06 Plastic length: D=2.4mm



PCB LAYOUT

X1311FR-XX-C43D24	PA6T 94V-0	Brass	1U"Gold	X1311W
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司

生	日期
发	
Δ	
文件工程章	

REVISIONS

DATE	REVISED	APPROVED
------	---------	----------

www.xkb.cn www.hellixkb.com www.hellixkb.cn

DSND	DATE	SCALE: N/A	MODEL TYPE: X1311FR-XX-C43D24
DWN	DATE	VIEW: ①	PART NO.: 1.27mm Crimp Style Connector
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g SHEET 1/1 REVISION A0

ANGULAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)