



PCB LAYOUT

Specifications:

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:1A AC/DC  
 额定电流: 1A AC/DC  
 Withstanding voltage:300V AC/minute  
 耐受电压: 300V AC/分钟  
 Temperature range:-40°C-+105°C  
 温度范围: -40°C-+105°C  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:≤20mΩ  
 接触电阻: ≤20mΩ  
 Material:PA6T UL94V-0  
 材质: PA6T UL94V-0  
 Plating Category:1U"Gold  
 镀层: 1U"Gold  
 Wave soldering temperature:255±5°C, 10S  
 波峰焊温度: 255±5°C, 10S

X1311 W R - XX J - C40 D24  
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:W-Wafer
- 3.Welding Board Angle:R-Straight 90°
- 4.Row No.Pin No:XX Pin
- 5.Plastic height:J=1.0 mm
- 6.Pin Length:C=4.0mm
- 7.Pin Length:D=2.4

|                    |          |               |                     |
|--------------------|----------|---------------|---------------------|
| X1311WR-XXJ-C40D24 | PA6T     | Brass         | X1311F              |
| PART NO            | Material | Material(Pin) | Suitable XKB Female |

广东星坤科技股份有限公司

|       |             |      |         |          |   |      |
|-------|-------------|------|---------|----------|---|------|
| ΔX    | 日期          |      |         |          | ANGULAR                                       | ±5°  |
| ΔX    |             |      |         |          | L ≤ 4   | ±0.2 |
| ΔX    |             |      |         |          | 4 < L ≤ 16                                    | ±0.3 |
| MARK  | DESCRIPTION | DATE | REVISED | APPROVED | 16 < L ≤ 63                                   | ±0.4 |
| 文件工程章 | REVISIONS   |      |         |          | L > 63  | ±0.5 |
|       |             |      |         |          | UNSPECIFIED TOLERANCES                        |      |
|       |             |      |         |          | www.helloxkb.com www.helloxkb.cn www.xk-dg.cn |      |



|                                       |             |                                     |
|---------------------------------------|-------------|-------------------------------------|
| DSND                                  | SCALE: N/A  | MODEL TYPE:<br>1.27mm BTB Connector |
| DWN                                   | VIEW:       | PART NO.:<br>X1311WR-XXJ-C40D24     |
| CHKD                                  | UNIT: mm/in | DWG NO.:<br>X-X1311WR-XXJ-C40D24    |
| APPD                                  | SIZE: A4    | WEIGHT                              |
| XKB INDUSTRIAL PRECISION CO., LIMITED |             | SHEET                               |
|                                       |             | REVISION                            |
|                                       |             | 1/1                                 |
|                                       |             | A0                                  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)