



PCB LAYOUT

Specifications:

规格:

- Voltage rating: 250V AC/DC
- 额定电压: 250V AC/DC
- Current rating: 1A AC/DC
- 额定电流: 1A AC/DC
- Withstanding voltage: 300V AC/minute
- 耐受电压: 300V AC/分钟
- Temperature range: -40°C +105°C
- 温度范围: -40°C +105°C
- Insulation resistance: ≥1000MΩ
- 绝缘电阻: ≥1000MΩ
- Contact resistance: ≤20mΩ
- 接触电阻: ≤20mΩ
- Material: PA6T UL94V-0
- 材质: PA6T UL94V-0
- Plating Category: 1U"Gold
- 镀层: 1U"Gold
- Wave soldering temperature: 255±5°C, 10S
- 波峰焊温度: 255±5°C, 10S

X1311 W V - XX J - C40 D24
 ① ② ③ ④ ⑤ ⑥ ⑦

1. Series No
2. Category: W-Wafer
3. Welding Board Angle: V-Stright 180°
4. Row No. Pin No: XX Pin
5. Plastic height: J=1.0 mm
6. Pin Length: C=4.0mm
7. Pin Length: D=2.4

| | | | |
|--------------------|----------|---------------|---------------------|
| X1311WV-XXJ-C40D24 | PA6T | Brass | X1311F |
| PART NO | Material | Material(Pin) | Suitable XKB Female |

广东星坤科技股份有限公司

| | | | | | | |
|-------|-------------|------|---------|----------|---|------|
| Δ* | 日期 | | | | ANGLAR | ±5° |
| Δ* | | | | | L ≤ 4 | ±0.2 |
| Δ* | | | | | 4 < L ≤ 16 | ±0.3 |
| MARK | DESCRIPTION | DATE | REVISED | APPROVED | 16 < L ≤ 63 | ±0.4 |
| 文件工程章 | REVISIONS | | | | L > 63 | ±0.5 |
| | | | | | UNSPECIFIED TOLERANCES | |
| | | | | | www.helloxkb.com www.helloxkb.cn www.xk-dg.cn | |



| | | | |
|---------------------------------------|--|-------------|-------------------------------------|
| DSND | | SCALE: N/A | MODEL TYPE: 1.27mm BTB Connector |
| DWN | | VIEW: | PART NO.: X1311WV-XXJ-C40D24 |
| CHKD | | UNIT: mm/in | DWG NO.: X-X1311WV-XXJ-C40D24 |
| APPD | | SIZE: A4 | |
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT |
| | | | SHEET |
| | | | REVISION |
| | | | 1/1 |
| | | | A0 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)