



P.C.B LAYOUT

Specifications:  
 规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:1A AC/DC  
 额定电流: 1A AC/DC  
 Withstanding voltage:300V AC/minute  
 耐受电压: 300V AC/分钟  
 Temperature range:-40°C~+105°C  
 温度范围: -40°C~+105°C  
 Insulation resistance:≥500MΩ  
 绝缘电阻: ≥500MΩ  
 Contact resistance:≤20mΩ  
 接触电阻: ≤20mΩ  
 Material:PA6T UL94V-0  
 材质: PA6T UL94V-0  
 Plating Category:1U"Gold  
 镀层: 1U"Gold  
 Wave soldering temperature:255±5°C, 10S  
 波峰焊温度: 255±5°C, 10S

X1321 W V - 2xXX J - C40 D18  
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:W-Wafer
- 3.Welding Board Angle:V-Strighr 180°
- 4.Row No.Pin No:2xXX-2x01~2x40Pin
- 5.Plastic Height:J=1.0mm
- 6.Pin Length:C=4.0mm
- 7.Pin Length:D=1.8mm

|                      |          |               |                     |
|----------------------|----------|---------------|---------------------|
| X1321WV-2xXXJ-C40D18 | PA6T     | Brass         | X1321F              |
| PART NO              | Material | Material(Pin) | Suitable XKB Female |

广东星坤科技股份有限公司

|   |             |      |         |          |      |                        |      |
|---|-------------|------|---------|----------|------|------------------------|------|
| DATE  | DATE        | DATE | DATE    | DATE     | DATE | ANGLAR                 | ±5°  |
| Δ   | Δ           | Δ    | Δ       | Δ        | Δ    | L ≤ 4                  | ±0.2 |
| Δ   | Δ           | Δ    | Δ       | Δ        | Δ    | 4 < L ≤ 16             | ±0.3 |
| Δ   | Δ           | Δ    | Δ       | Δ        | Δ    | 16 < L ≤ 63            | ±0.4 |
| MARK  | DESCRIPTION | DATE | REVISED | APPROVED |      | L > 63                 | ±0.5 |
| REVISIONS                                     |             |      |         |          |      | UNSPECIFIED TOLERANCES |      |
| www.helloxkb.com www.helloxkb.cn www.xk-dg.cn |             |      |         |          |      |                        |      |



|                                       |             |                                     |       |          |
|---------------------------------------|-------------|-------------------------------------|-------|----------|
| DSND                                  | SCALE: N/A  | MODEL TYPE:<br>1.27mm BTB Connector |       |          |
| DWN                                   | VIEW:       | PART NO.:<br>X1321WV-2xXXJ-C40D18   |       |          |
| CHKD                                  | UNIT: mm/in | DWG NO.:<br>X-X1321WV-2xXXJ-C40D18  |       |          |
| APPD                                  | SIZE: A4    | WEIGHT                              | SHEET | REVISION |
| XKB INDUSTRIAL PRECISION CO., LIMITED |             |                                     | 1/1   | A0       |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)