



■ Specifications :

- Voltage rating: 100V AC / DC
- Current rating: 2A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ

X2016 H- XX-N0

① ② ③ ④

- ① Series Number
- ② Category : H-HSG
- ③ Row No. Pin No: xx-02-15P
- ④ Material: N0-PA66 UL 94V-0

| Poles | Dimensions(mm) |       |       | Poles | Dimensions(mm) |       |       |
|-------|----------------|-------|-------|-------|----------------|-------|-------|
|       | A              | B     | C     |       | A              | B     | C     |
| 02    | 2.00           | 5.80  | 4.60  | 12    | 22.00          | 25.80 | 24.60 |
| 03    | 4.00           | 7.80  | 6.60  | 13    | 24.00          | 27.80 | 26.60 |
| 04    | 6.00           | 9.80  | 8.60  | 14    | 26.00          | 29.80 | 28.60 |
| 05    | 8.00           | 11.80 | 10.60 | 15    | 28.00          | 31.80 | 30.60 |
| 06    | 10.00          | 13.80 | 12.60 | 16    | 30.00          | 33.80 | 32.60 |
| 07    | 12.00          | 15.80 | 14.60 | 17    | 32.00          | 35.80 | 34.60 |
| 08    | 14.00          | 17.80 | 16.60 | 18    | 34.00          | 37.80 | 36.60 |
| 09    | 16.00          | 19.80 | 18.60 | 19    | 36.00          | 39.80 | 38.60 |
| 10    | 18.00          | 21.80 | 20.60 | 20    | 38.00          | 41.80 | 40.60 |
| 11    | 20.00          | 23.80 | 22.60 |       |                |       |       |

| X2016H-XX-N0 | PA66 UL 94V-0 | X2016T                | X2016W                |
|--------------|---------------|-----------------------|-----------------------|
| PARY NO      | Material      | Suitable XKB Terminal | Suitable XKB Terminal |

广东星坤科技股份有限公司

生效

| ΔX   | 日期          |
|------|-------------|
| ΔX   | 日期          |
| ΔX   | 日期          |
| MARK | DESCRIPTION |

文件工程章

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

| ANGLAR      | ±5°  |
|-------------|------|
| L ≤ 4       | ±0.2 |
| 4 < L ≤ 16  | ±0.3 |
| 16 < L ≤ 63 | ±0.4 |
| L > 63      | ±0.5 |

UNSPECIFIED TOLERANCES

|                                       |      |             |   |
|---------------------------------------|------|-------------|---|
| DSND                                  | DATE | SCALE: N/A  | MODEL TYPE:<br>X2016H-XX-N0               |
| DWN                                   | DATE | VIEW:       | PART NO.:<br>2.0mm Crimp Style Connectors |
| CHKD                                  | DATE | UNIT: mm/in | DWG NO.:                                  |
| APPD                                  | DATE | SIZE: A4    |   |
| XKB INDUSTRIAL PRECISION CO., LIMITED |      |             | WEIGHT<br>1.0g                            |
|                                       |      |             | SHEET<br>1/1                              |
|                                       |      |             | REVISION<br>A0                            |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)  
[001000](#)