



Specifications:

规格:

Voltage rating:250V AC/DC

额定电压: 250V AC/DC

Current rating:3A AC/DC

额定电流: 3A AC/DC

Withstanding voltage:1000V AC/minute

耐受电压: 1000V AC/分钟

Temperature range:-25℃~+85℃

温度范围: -25℃~+85℃

Insulation resistance:≥1000MΩ

绝缘电阻: ≥1000MΩ

Contact resistance:≤30mΩ

接触电阻: ≤30mΩ

After environmental testing:≤50mΩ

环境测试后: ≤50兆欧

X2026 H X- 2xXX D-N0 XX

① ② ③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:H-HSG
- 3.Appearance type:Blank-Ordinary
- 4.Row No-Pin No:2xXX-2x02P~2x16P
- 5.Plug the Pin&Special N0:
D-With Lock in the middle
- 6.Material:N0-PA66 94V-0
- 7.Color:Blank-Natural Color

poles	Dimensions(mm)			poles	Dimensions(mm)			poles	Dimensions(mm)		
	A	B	C		A	B	C		A	B	C
2x02	2.00	4.60	6.76	2x10	18.00	20.60	22.76	2x18	34.00	36.60	38.76
2x03	4.00	6.60	8.76	2x11	20.00	22.60	24.76	2x19	36.00	38.60	40.76
2x04	6.00	8.60	10.76	2x12	22.00	24.60	26.76	2x20	38.00	40.60	42.76
2x05	8.00	10.60	12.76	2x13	24.00	26.60	28.76				
2x06	10.00	12.60	14.76	2x14	26.00	28.60	30.76				
2x07	12.00	14.60	16.76	2x15	28.00	30.60	32.76				
2x08	14.00	16.60	18.76	2x16	30.00	32.60	34.76				
2x09	16.00	18.60	20.76	2x17	32.00	34.60	36.76				

X2026H-2xXXD-N0	Nylon 66 UL 94-V0	X2026T-D	X2026H-D
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

生效	日期
ΔX	
ΔX	
ΔX	
MARK	
文件工程章	

DESCRIPTION	DATE	REVISED	APPROVED	units:	mm
				tolerance:	
				X.X	±0.2mm
				X.XX	±0.1mm
				X.XXX	±0.05mm
					UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A
DWN		DATE		VIEW:
CHKD		DATE		UNIT: mm/in
APPD		DATE		SIZE: A4
XKB INDUSTRIAL PRECISION CO., LIMITED				

MODEL TYPE: Wire to board connector		
PART NO.: 2.00mm Crimp Style Connectors		
DWG NO.: X2026H-2xXXD-N0		
WEIGHT	SHEET	REVISION
1.0g	1/1	A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)