



Specifications:

规格:

Voltage rating:250V AC/DC

额定电压: 250V AC/DC

Current rating:3A AC/DC

额定电流: 3A AC/DC

Withstanding voltage:1000V AC/minute

耐受电压: 1000V AC/分钟

Temperature range:-25℃~+85℃

温度范围: -25℃~+85℃

Insulation resistance:≥1000MΩ

绝缘电阻: ≥1000MΩ

Contact resistance:≤30mΩ

接触电阻: ≤30mΩ

After environmental testing:≤50mΩ

环境测试后: ≤50兆欧

X2026 W V S-2xXXD1-46SN

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- 1.Series No
- 2.Category:W-WAFER
- 3.Welding Board Angle:V-Straight 180°
- 4.Welding Way:S-SMT
- 5.Row No-Pin No:2xXX-2x02P~2x30P
- 6.Plug the Pin&Special NO:  
D1-With Lock in the middle
- 7.Material:46-PA46 94V-0
- 8.Plating Category:SN-Bright Tin Plating

| poles | Dimensions(mm) |       |       | poles | Dimensions(mm) |       |       | Poles | Dimensions(mm) |       |       |
|-------|----------------|-------|-------|-------|----------------|-------|-------|-------|----------------|-------|-------|
|       | A              | B     | C     |       | A              | B     | C     |       | A              | B     | C     |
| 2x02  | 2.00           | 6.00  | 4.90  | 2x10  | 18.00          | 22.00 | 20.90 | 2x18  | 34.00          | 38.00 | 36.90 |
| 2x03  | 4.00           | 8.00  | 6.90  | 2x11  | 20.00          | 24.00 | 22.90 | 2x19  | 36.00          | 40.00 | 38.90 |
| 2x04  | 6.00           | 10.00 | 8.90  | 2x12  | 22.00          | 26.00 | 24.90 | 2x20  | 38.00          | 42.00 | 40.90 |
| 2x05  | 8.00           | 12.00 | 10.90 | 2x13  | 24.00          | 28.00 | 26.90 | 2x30  | 58.00          | 62.00 | 60.90 |
| 2x06  | 10.00          | 14.00 | 12.90 | 2x14  | 26.00          | 30.00 | 28.90 |       |                |       |       |
| 2x07  | 12.00          | 16.00 | 14.90 | 2x15  | 28.00          | 32.00 | 30.90 |       |                |       |       |
| 2x08  | 14.00          | 18.00 | 16.90 | 2x16  | 30.00          | 34.00 | 32.90 |       |                |       |       |
| 2x09  | 16.00          | 20.00 | 18.90 | 2x17  | 32.00          | 36.00 | 34.90 |       |                |       |       |

|                      |            |               |             |                       |
|----------------------|------------|---------------|-------------|-----------------------|
| X2026VWS-2xXXD1-46SN | PA46 94V-0 | Brass         | Tin-Plated  | X2026H-D              |
| PART NO              | Material   | Material(pin) | Finish(Pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司  
Recommended Pin Layout  
General Tolerance±0.05

|      |       |              |                  |                 |          |                        |
|------|-------|--------------|------------------|-----------------|----------|------------------------|
| 生    | 日期    |              |                  |                 |          | units: mm              |
| ΔX   |       |              |                  |                 |          | tolerance: X.X ±0.2mm  |
| ΔX   |       |              |                  |                 |          | X.XX ±0.1mm            |
| ΔX   |       |              |                  |                 |          | X.XXX ±0.05mm          |
| MARK | 文件工程章 | DESCRIPTION  | DATE             | REVISED         | APPROVED | UNSPECIFIED TOLERANCES |
|      |       | REVISIONS    |                  |                 |          |                        |
|      |       | www.xk-dg.cn | www.helloxkb.com | www.helloxkb.cn |          |                        |

|                                       |  |      |  |             |  |          |
|---------------------------------------|--|------|--|-------------|--|----------|
| DSND                                  |  | DATE |  | SCALE: N/A  | MODEL TYPE:<br>Wire to board connector     |          |
| DWN                                   |  | DATE |  | VIEW:       | PART NO.:<br>2.00mm Crimp Style Connectors |          |
| CHKD                                  |  | DATE |  | UNIT: mm/in | DWG NO.:<br>X2026VWS-2xXXD1-9TSN           |          |
| APPD                                  |  | DATE |  | SIZE: A4    |  |          |
| XKB INDUSTRIAL PRECISION CO., LIMITED |  |      |  | WEIGHT      | SHEET                                      | REVISION |
|                                       |  |      |  | 1.0g        | 1/1  | A0       |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)