




■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing: ≤20mΩ

X2510WR-XX-N0SN

① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Category: W-WAFER
- ③ Welding Board Angle: R-90°
- ④ Row No.-Pin No.: XX-Single Row
- ⑤ Material: N0 -PA66 94V-0
- ⑥ Plating Category: SN-Bright Tin Plating



Recommad PCB Layout

| Poles | Dimensions(mm) | | Poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B |
| 02 | 2.54 | 5.08 | 10 | 22.86 | 25.4 |
| 03 | 5.08 | 7.62 | 11 | 25.4 | 27.94 |
| 04 | 7.62 | 10.16 | 12 | 27.94 | 30.48 |
| 05 | 10.16 | 12.7 | 13 | 30.48 | 33.02 |
| 06 | 12.7 | 15.24 | 14 | 33.02 | 35.56 |
| 07 | 15.24 | 17.78 | 15 | 35.56 | 38.1 |
| 08 | 17.78 | 20.32 | | | |
| 09 | 20.32 | 22.86 | | | |

| | | | | |
|-----------------|-------------------|---------------|-------------|------------------------|
| X2510WR-XX-N0SN | Nylon 66 UL 94V-0 | Brass | Tin-Plated | X2510H |
| PART NO | Material | Material(Pin) | Finish(Pin) | Mates With XKB Housing |

For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
 香港星坤工業精密有限公司

| | | | | | | | |
|------|-------------------------|------|---------|----------|---------------------------------------|------|--|
| △ X | | | | | ANGULAR | ±5° | |
| △ X | | | | | L ≤ 4 | ±0.2 | |
| △ X | | | | | 4 < L ≤ 16 | ±0.3 | |
| MARK | | | | | 16 < L ≤ 63 | ±0.4 | |
| | | | | | L > 63 | ±0.5 | |
| | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES | | |
| | Authorized Signature(s) | | | | XKB INDUSTRIAL PRECISION CO., LIMITED | | |

| | | | | | | | |
|------|--|------|--|------------|--------------------------------|-------|----------|
| DSND | | DATE | | SCALE: N/A | MODEL TYPE: | | |
| DWN | | DATE | | VIEW: | X2510WR-XX-N0SN | | |
| CHKD | | DATE | | UNIT: mm | 2.54 mm Crimp Style Connectors | | |
| APPD | | DATE | | SIZE: A4 | DWG NO.: | | |
| | | | | | WEIGHT | SHEET | REVISION |
| | | | | | 1.0g | 1/1 | A0 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)