


Specifications:

规格:
 Voltage rating:400V AC/DC
 额定电压: 400V AC/DC
 Current rating:10A AC/DC
 额定电流: 10A AC/DC
 Withstanding voltage:1800V AC/minute
 耐受电压: 1800V AC/分钟
 Temperature range:-40°C~+105°C
 温度范围: -40°C~+105°C
 Insulation resistance:100MΩ min
 绝缘电阻: 100MΩ Min
 Contact resistance:10mΩ Max
 接触电阻: 10mΩ Max


X2513 H - XX X - N0

① ② ③ ④ ⑤


1. Series No
2. Category:H-Housing
3. Row No.Pin No:XX-02~08P
4. Special No:A-A Key(Black);B-B Key(Natural)
5. Material:N0-PA66 94V-0





2PIN




3PIN




4PIN




5PIN



6PIN



7PIN



8PIN

| Poles | Dimensions(mm) | |
|-------|----------------|-------|
| | A | B |
| 02 | 7.70 | 2.50 |
| 03 | 10.20 | 5.00 |
| 04 | 12.70 | 7.50 |
| 05 | 15.20 | 10.00 |
| 06 | 17.70 | 12.50 |
| 07 | 20.20 | 15.00 |
| 08 | 22.70 | 17.50 |

| | | | |
|---------------|----------|--------------------|-----------------------|
| X2513H-XXX-N0 | PA66 | X2513W | X2513T |
| PART NO | Material | Suitable XKB Wafer | Suitable XKB Terminal |

| | | |
|------|-------------|---------------------------------------------|
| DSND | SCALE: N/A | MODEL TYPE: 2.50mm Crimp Style Connector |
| DWN | VIEW: | PART NO.: X2513H-XXX-N0 |
| CHKD | UNIT: mm/in | DWG NO.: X-X2513H-XXX-N0 |
| APPD | SIZE: A4 | WEIGHT SHEET REVISION |
| | | 1/1 A0 |



XKB INDUSTRIAL PRECISION CO.,LIMITED

| | |
|------------------------|------|
| ANGLAR | ±5° |
| L ≤ 4 | ±0.2 |
| 4 < L ≤ 16 | ±0.3 |
| 16 < L ≤ 63 | ±0.4 |
| L > 63 | ±0.5 |
| UNSPECIFIED TOLERANCES | |

| | | | | | |
|-----------|-------------|------|---------|----------|--|
| ΔX | | | | | |
| ΔX | | | | | |
| ΔX | | | | | |
| MARK | DESCRIPTION | DATE | REVISED | APPROVED | |
| REVISIONS | | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)