

Specifications:



规格:

- Voltage rating: 600V AC/DC
- 额定电压: 600V AC/DC
- Current rating: 7A AC/DC
- 额定电流: 7A AC/DC
- Withstanding voltage: 1500V AC/minute
- 耐受电压: 1500V AC/分钟
- Temperature range: -40°C-+125°C
- 温度范围: -40°C-+125°C
- Insulation resistance: 1000MΩ min
- 绝缘电阻: 1000MΩ min
- Contact resistance: 20mΩ max
- 接触电阻: 20mΩ max

X4140 T F - B SN

① ②③④ ⑤

1. Series No
2. Category: T-Terminal
3. Category: F-Female Terminal
4. Material: B-Brass
5. Finish: SN-Tin-plated



X4140TF-BSN	Brass	Tin-plated	AWG22#-26#	X4140HM
PART NO	Material	Finish	Wire Range	Suitable XKB Housing

DSND	SCALE: N/A	MODEL TYPE: 4.14mm Crimp Style Connector
DWN	VIEW:	PART NO.: X4140TF-BSN
CHKD	UNIT: mm/in	DWG NO.: X-X4140TF-BSN
APPD	SIZE: A4	

					ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5
REVISIONS					UNSPECIFIED TOLERANCES	



XKB INDUSTRIAL PRECISION CO., LIMITED

WEIGHT	SHEET	REVISION
	1/1	A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-](#)
[002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#) [820-22-008-30-001101](#)
[821-22-002-10-001101](#) [821-22-003-10-002101](#)