



P.C.B LAYOUT

**Specifications:**  
 规格:  
**Voltage rating:**250V AC/DC  
 额定电压: 250V AC/DC  
**Current rating:**2A AC/DC  
 额定电流: 2A AC/DC  
**Withstanding voltage:**1000V AC/minute  
 耐受电压: 1000V AC/分钟  
**Temperature range:**-40°C-+105°C  
 温度范围: -40°C-+105°C  
**Insulation resistance:**≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
**Contact resistance:**≤20mΩ  
 接触电阻: ≤20mΩ  
**Material:**PA6T UL94V-0  
 材质: PA6T UL94V-0  
**Plating Category:**1U"Gold  
 镀层: 1U"Gold  
**Wave soldering temperature:**255±5°C, 10S  
 波峰焊温度: 255±5°C, 10S

X4621 W R - 2xXX I - C40 D28  
 ① ② ③ ④ ⑤ ⑥ ⑦

- 1. Series No
- 2. Category:W-Wafer
- 3. Welding Board Angle:R-Stright 90°
- 4. Row No.Pin No:2xXX-2x01~2x40P
- 5. Plastic Height:l=2.0mm
- 6. Pin Length:C=4.0mm
- 7. Pin Length:D=2.8mm

X4621WR-2xXXI-C40D28	PA6T	Brass	X4621F
PART NO	Material	Material(Pin)	Suitable XKB Female

广东星坤科技股份有限公司

Δ#	日期					ANGLAR	±5°
Δ#						L ≤ 4	±0.2
Δ#						4 < L ≤ 16	±0.3
Δ#						16 < L ≤ 63	±0.4
MARK	DESCRIPTION	DATE	REVISED	APPROVED		L > 63	±0.5
文件工程章						UNSPECIFIED TOLERANCES	
REVISIONS						XKB INDUSTRIAL PRECISION CO., LIMITED	
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						WEIGHT SHEET REVISION	
						1/1 A0	



DSND		SCALE: N/A	MODEL TYPE: 2.0mm BTB Connector
DWN		VIEW:	PART NO.: X4621WR-2xXXI-C40D28
CHKD		UNIT: mm/in	DWG NO.: X-X4621WR-2xXXI-C40D28
APPD		SIZE: A4	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)