






For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
 香港星洲工業精密有限公司

REVISIONS
 Authorized Signature(s)

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|------|-------------|------|---------|----------|------------------------|
| △ X | | | | | L > 63 ± 0.5 |
| △ X | | | | | 16 < L ≤ 63 ± 0.4 |
| △ X | | | | | 4 < L ≤ 16 ± 0.3 |
| | | | | | L ≤ 4 ± 0.2 |
| | | | | | ANGULAR ± 5° |

| DATE | SCALE: N/A | MODEL TYPE: X6521FV-2*XX-C85D32 | DWN | DATE | VIEW:  | PART NO.: | CHKD | DATE | UNIT: mm | SIZE: A4 | WEIGHT: 1.0g | SHEET: 1/1 | REVISION: A0 |
|------|------------|---------------------------------|------|------|---|-----------|------|------|----------|----------|--------------|------------|--------------|
| | | | APPD | | | | | | | | | | |

P.C.B LAYOUT



| PART NO | Material | Material(Pin) | Finish(Pin) | Suitable XKB Terminal |
|---------------------|------------|---------------|-------------|-----------------------|
| X6521FV-2*XX-C85D32 | PA6T 94V-0 | Brass | 1U"Gold | X6521W |

- ① Series No.
- ② Category: F-Female
- ③ Welding Board Angle: V-Stright 180°
- ④ Row No -Pin No : 2*XX-2*01P-40P
- ⑤ Plastic height: C=8.5mm
- ⑥ Pin length: D=3.2mm

X6521 F V - 2*XX - C85 D32
 ① ② ③ ④ ⑤ ⑥

- Specifications :**
- Voltage rating: 250VAC / DC
 - Current rating: 3A AC / DC
 - Withstanding voltage: 1000V AC/minute
 - Temperature range: -40 to +105
 - Insulation resistance: ≥1000M Min
 - Contact resistance: ≤20M Max
 - Material: PBT 94V-0
 - Plating Category: 1U"Gold
 - Wave soldering temperature: 255±5°C, 10s

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)