



XKB Connectivity

规格 Specifications

- 额定电压 Voltage rating:500V AC/DC
- 额定电流 Current rating:1A AC/DC
- 耐电压 Withstanding voltage: 500V AC/minute
- 温度区间 Temperature range:-40°C~+105°C
- 绝缘电阻 Insulation resistance:≥1000MΩ
- 接触电阻 Contact resistance: ≤10mΩ
- 环境测试后 After environmental testing:≤20mΩ

XKB Connectivity

X9127 W V S-XX A1- 9T SN XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Category:W-wafer
- ③ Welding Board Angle:V- Straight 180°
- ④ Welding Way:S-SMT
- ⑤ Row No.-Pin No.:XX-04P~26P
- ⑥ Plug the Pin &Special No.:A1-With Single Gap
- ⑦ Material:9T-Nylon 9T 94V-0
- ⑧ Planting Category:SN-Bright tin plating
- ⑨ Color: RE-Red RD-purplish red

XKB Connectivity

| Poles | Dimensions(mm) | | | Poles | Dimensions(mm) | | |
|-------|----------------|-------|-------|-------|----------------|-------|-------|
| | A | B | C | | A | B | C |
| 4 | 3.81 | 7.00 | 5.60 | 16 | 19.05 | 22.24 | 20.84 |
| 6 | 6.35 | 9.54 | 8.14 | 18 | 21.59 | 24.78 | 23.38 |
| 8 | 8.89 | 12.08 | 10.68 | 20 | 24.13 | 27.32 | 25.92 |
| 10 | 11.43 | 14.62 | 13.22 | 22 | 26.67 | 29.86 | 28.46 |
| 12 | 13.97 | 17.16 | 15.76 | 24 | 29.21 | 32.40 | 31.00 |
| 14 | 16.51 | 19.70 | 18.30 | 26 | 31.75 | 34.94 | 33.54 |

XKB Connectivity

| | | | | |
|----------------------|--------------|---------------|---------------|-------------|
| X9127WVS-XXA1-9TSNRD | Purplish red | PA9T UL 94V-0 | Brass | Tin-Plated |
| X9127WVS-XXA1-9TSNRE | RED | | | |
| PART NO | Color | Material | Material(Pin) | Finish(Pin) |

Recommended PCB Layout(Top Side)
(PCB Board Tolerance±0.05)
XKB Connectivity

广东星坤科技股份有限公司

生 效 日期
文件工程章

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|------|-------------|------|---------|----------|------------------------|
| | | | | | ANGULAR ±5° |
| | | | | | L ≤ 4 ±0.2 |
| | | | | | 4 < L ≤ 16 ±0.3 |
| | | | | | 16 < L ≤ 63 ±0.4 |
| | | | | | L > 63 ±0.5 |

| | | | |
|---------------------------------------|------|-------------|-------------------------------------------|
| DSND | DATE | SCALE: N/A | MODEL TYPE: X9127WVS-XXA1-9TSNXX |
| DWN | DATE | VIEW: | PART NO.: 1.27mm Crimp Style Connector |
| CHKD | DATE | UNIT: mm/in | DWG NO.: |
| APPD | DATE | SIZE: A4 | |
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT 1.0g |
| | | | SHEET 1/1 |
| | | | REVISION A0 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)