




4.20 [0.165]



4.20 [0.165]



Specifications xxb

规格:

Voltage rating: 600V AC/DC

额定电压: 600V AC/DC

Current rating: 9A AC/DC

额定电流: 9A AC/DC

Withstanding voltage: 1500V AC/minute

耐受电压: 1500V AC/分钟

Temperature

range: -25°C +85°C

温度范围: -25°C +85°C

Insulation resistance: ≥100MΩ

绝缘电阻: ≥100MΩ xxb

Contact resistance: ≤10mΩ

接触电阻: ≤10mΩ

After environmental

testing: ≤20mΩ

环境测试后: ≤20兆欧

X9357WVX-2*XXX-XX XXXX

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦
- ⑧
- ⑨

1 Series No.

2 Category: W-AFER

3 Welding Board Angle: V- Stright 180°

4 Weding Way: Blank-DIP

5 Row No Pin No: 2*XX-2*01P-2*12P

6 Plug the Pin & Special No.:

G-Join The glass fiber 15%

7 Material: N0-PAG6 94V-0; N2-PA66 94V-2

9T-PA9T94V-0; 46-PA46 94V-0

8 Plating Category: SN-Bright Tin Plating

9 Color: Blank-Natural Color BK-Black GY-Gray

| Poles | Dimensions(mm) | | Poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B |
| 2*01 | 5.40 | - | 2*07 | 30.60 | 25.20 |
| 2*02 | 9.60 | 4.20 | 2*08 | 34.80 | 29.40 |
| 2*03 | 13.80 | 8.40 | 2*09 | 39.00 | 33.60 |
| 2*04 | 18.00 | 12.60 | 2*10 | 43.20 | 37.80 |
| 2*05 | 22.20 | 16.80 | 2*11 | 47.40 | 42.00 |
| 2*06 | 26.40 | 21.00 | 2*12 | 51.60 | 46.20 |

| | | | | | |
|----------------------|-------------------------|---------------|-------------|--------|-----------------------|
| X9357WV-2XX-9T5W | Nylon 9T UL 94V-0 | Brass | Matte bn | X9357H | |
| X9357WV-2*XX-N2V01 | Nylon 66 UL 94V-2 | Brass | Gold-Flash | | |
| X9357WV-2*XX-N2S1N | Nylon 66 UL 94V-2 | Brass | Tin-Plated | | |
| X9357WV-2*XX-G-N2V01 | Nylon 66 UL 94V-2 GF15% | Brass | Gold-Flash | | |
| X9357WV-2*XX-G-N2S1N | Nylon 66 UL 94V-2 GF15% | Brass | Tin-Plated | | |
| PART NO | Material | Material(Pin) | Finish(Pin) | | Suitable XKB Terminal |

广东星坤科技股份有限公司

| | |
|-------|----|
| 生 | 日期 |
| 发 | |
| Δ | |
| 文件工程章 | |

REVISIONS
www.heloxkb.com

| XKB | | DSND | DATE | SCALE: NA | MODEL TYPE: |
|------------------------|------|------|------|-------------|-------------------------------|
| ANGLAR | ±5° | DWNN | DATE | VIEW: | X9357WV-2*XXX-XXXX |
| L ≤ 4 | ±0.2 | CHKD | DATE | UNIT: mm/in | PART NO.: |
| 4 < L ≤ 16 | ±0.3 | APPD | DATE | SIZE: A4 | 4.2 mm Crimp Style Connectors |
| 16 < L ≤ 63 | ±0.4 | | | | DWG NO.: |
| L > 63 | ±0.5 | | | | |
| UNSPECIFIED TOLERANCES | | | | | |

| | | | | | |
|---------------------------------------|--|--|--------|-------|----------|
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT | SHEET | REVISION |
| | | | 1.0g | 1/1 | A0 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)