



■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 7A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance:  $\geq 1000M \Omega$
- Contact resistance:  $\leq 10m\Omega$
- After environmental testing :  $\leq 20m\Omega$

X9396 H -XX- N0-X  
① ② ③ ④ ⑤

- ① Series No.
- ② Category : H-HSG
- ③ Row No.Pin No.XX-02-15
- ④ Material:N0-PA66 94V-0
- ⑤ C-Resistance to glowing filament

| Poles | Dimensions(mm) |       | Poles | Dimensions(mm) |       |
|-------|----------------|-------|-------|----------------|-------|
|       | A              | B     |       | A              | B     |
| 02    | 3.96           | 8.30  | 09    | 31.68          | 36.30 |
| 03    | 7.92           | 12.30 | 10    | 35.64          | 40.30 |
| 04    | 11.88          | 16.30 | 11    | 39.60          | 44.30 |
| 05    | 15.84          | 20.30 | 12    | 43.56          | 48.30 |
| 06    | 19.80          | 24.30 | 13    | 47.52          | 52.30 |
| 07    | 23.76          | 28.30 | 14    | 51.48          | 56.30 |
| 08    | 27.72          | 32.30 | 15    | 55.44          | 60.30 |

|                |                   |                       |                       |
|----------------|-------------------|-----------------------|-----------------------|
| X9396H-XX-N0-C | Nylon 66 UL 94V-0 | X9396T                | X9396W                |
| X9396H-XX-N0   | Nylon 66 UL 94V-0 |                       |                       |
| PART NO        | Material          | Suitable XKB Terminal | Suitable XKB Terminal |

广东星坤科技股份有限公司

生效

| MARK | DESCRIPTION | DATE | REVISED | APPROVED |
|------|-------------|------|---------|----------|
| ΔX   |             |      |         |          |
| ΔX   |             |      |         |          |
| ΔX   |             |      |         |          |

日期

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

文件工程章

|             |      |
|-------------|------|
| ANGLAR      | ±5°  |
| L ≤ 4       | ±0.2 |
| 4 < L ≤ 16  | ±0.3 |
| 16 < L ≤ 63 | ±0.4 |
| L > 63      | ±0.5 |

UNSPECIFIED TOLERANCES

|                                       |      |             |  |
|---------------------------------------|------|-------------|--|
| DSND                                  | DATE | SCALE: N/A  | MODEL TYPE:<br>X9396H-XX-N0                |
| DWN                                   | DATE | VIEW:       | PART NO.:<br>3.96mm Crimp Style Connectors |
| CHKD                                  | DATE | UNIT: mm/in | DWG NO.:<br>X9396H-XX-N0                   |
| APPD                                  | DATE | SIZE: A4    |  |
| XKB INDUSTRIAL PRECISION CO., LIMITED |      |             | WEIGHT<br>1.0g                             |
|                                       |      |             | SHEET<br>1/1                               |
|                                       |      |             | REVISION<br>A0                             |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)  
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)