

For and on behalf of
KKB INDUSTRIAL PRECISION CO., LIMITED
 香港星坤工業精密有限公司

REVISIONS
 Authorized Signature(s)

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|------|-------------|------|---------|----------|------------------------|
| △ X | | | | | L > 63 ±0.5 |
| △ X | | | | | 16 > L ≤ 63 ±0.4 |
| △ X | | | | | 4 < L ≤ 16 ±0.3 |
| △ X | | | | | L ≤ 4 ±0.2 |
| | | | | | ANGULAR ±5° |





| REVISION | SHEET | WEIGHT | SIZE: A4 |
|----------|-------|--------|----------|
| A0 | 1/1 | 1.0g | |

| APPD | DATE | CHKD | DATE | DWN | DATE | DSND | DATE |
|------|------|------|------|-----|------|------|------|
| | | | | | | | |

| UNIT: mm | VIEW: | SCALE: N/A |
|----------|-------|------------|
| | | |

| PART NO.: | MODEL TYPE: |
|--------------------------------|-----------------|
| 3.96 mm Crimp Style Connectors | X9396WV-XX-46SN |

Recommend PCB Layout



| PART NO | Material | Material(Pin) | Finish(Pin) | Suitable XKB Terminal |
|-----------------|-------------------|---------------|-------------|-----------------------|
| X9396WV-XX-46SN | Nylon 46 UL 94V-0 | Brass | Tin-Plated | X9396H |

| Poles | Dimensions(mm) | | Poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B |
| 02 | 3.96 | 7.92 | 09 | 31.68 | 35.64 |
| 03 | 7.92 | 11.88 | 10 | 35.64 | 39.60 |
| 04 | 11.88 | 15.84 | 11 | 39.60 | 43.56 |
| 05 | 15.84 | 19.80 | 12 | 43.56 | 47.52 |
| 06 | 19.80 | 23.76 | 13 | 47.52 | 51.48 |
| 07 | 23.76 | 27.72 | 14 | 51.48 | 55.44 |
| 08 | 27.72 | 31.68 | 15 | 55.44 | 59.40 |

- ① Series No
 X9396 W V-XX-46 SN
- ② Category: W-WAFER
- ③ Welding Board Angle: V-180°
- ④ Row No.-Pin No.: XX-02P~15P
- ⑤ Plating Category: 46-PA46 94-V0
- ⑥ Plating Category: SN-Bright tin plating

- Specifications :
- Voltage rating: 250V AC / DC
 - Current rating: 7A AC / DC
 - Withstanding voltage: 1500V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance: ≥1000MΩ
 - Contact resistance: ≤10mΩ
 - After environmental testing: ≤20mΩ

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)