



Specifications:

规格:
Voltage rating:250V AC/DC
额定电压: 250V AC/DC
Current rating:3A AC/DC
额定电流: 3A AC/DC
Withstanding voltage:1500V AC/minute
耐受电压: 1500V AC/分钟
Temperature range:-25℃~+85℃
温度范围: -25℃~+85℃
Insulation resistance:≥1000MΩ
绝缘电阻: ≥1000MΩ
Contact resistance:≤20mΩ
接触电阻: ≤20mΩ
After environmental testing:≤30mΩ
环境测试后: ≤30兆欧

X9555 H X-2xXX E- PT XX

① ②③ ④ ⑤ ⑥ ⑦

- 1.Series No
- 2.Category:H-HSG
- 3.Welding Board Angle:Blank-ordinary
- 4.Row No-Pin No:2xXX-2x02P~2x32P
- 5.Special No:
E-Double convex one atop the other
With SWB Mark
- 6.Material:PT-PBT 94V-0
- 6.Color:Blank-Natural Color

| poles | Dimensions(mm) | | poles | Dimensions(mm) | | poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B | | A | B |
| 2x02 | 2.54 | 5.08 | 2x13 | 30.48 | 33.02 | 2x24 | 58.42 | 60.96 |
| 2x03 | 5.08 | 7.62 | 2x14 | 33.02 | 35.56 | 2x25 | 60.96 | 63.50 |
| 2x04 | 7.62 | 10.16 | 2x15 | 35.56 | 38.10 | 2x26 | 63.50 | 66.04 |
| 2x05 | 10.16 | 12.70 | 2x16 | 38.10 | 40.64 | 2x27 | 66.04 | 68.58 |
| 2x06 | 12.70 | 15.24 | 2x17 | 40.64 | 43.18 | 2x28 | 68.58 | 71.12 |
| 2x07 | 15.24 | 17.78 | 2x18 | 43.18 | 45.72 | 2x29 | 71.12 | 73.66 |
| 2x08 | 17.78 | 20.32 | 2x19 | 45.72 | 48.26 | 2x30 | 73.66 | 76.20 |
| 2x09 | 20.32 | 22.86 | 2x20 | 48.26 | 50.80 | 2x31 | 76.20 | 78.74 |
| 2x10 | 22.86 | 25.40 | 2x21 | 50.80 | 53.34 | 2x32 | 78.74 | 81.28 |
| 2x11 | 25.40 | 27.94 | 2x22 | 53.34 | 55.88 | | | |
| 2x12 | 27.94 | 30.48 | 2x23 | 55.88 | 58.42 | | | |

| | | | |
|-----------------|--------------|-----------------------|-----------------------|
| X9555H-2xXXE-PT | PBT UL 94V-0 | X9555T-A | X9555W |
| PART NO | Material | Suitable XKB Terminal | Suitable XKB Terminal |

广东星坤科技股份有限公司

| | |
|------|-------|
| 生 | 日期 |
| ΔX | ΔX |
| ΔX | ΔX |
| MARK | 文件工程章 |

| DATE | REVISED | APPROVED | units: mm |
|------|---------|----------|------------------------|
| | | | tolerance: X.X ±0.2mm |
| | | | X.XX ±0.1mm |
| | | | X.XXX ±0.05mm |
| | | | UNSPECIFIED TOLERANCES |

| | | | |
|---------------------------------------|------|-------------|---|
| DSND | DATE | SCALE: N/A | MODEL TYPE: Wire to board connector |
| DWN | DATE | VIEW: | PART NO.: 2.54mm Crimp Style Connectors |
| CHKD | DATE | UNIT: mm/in | DWG NO.: X9555H-2xXXE-PT |
| APPD | DATE | SIZE: A4 | WEIGHT: 1.0g |
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | SHEET: 1/1 |
| | | | REVISION: A0 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#)
[FCN-367T-T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-41-018-10-001000](#)