



**Specifications:**

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Withstanding voltage:600V AC/minute  
 耐受电压:600V AC/分钟  
 Temperature range:-25℃~+85℃  
 温度范围: -25℃~+85℃  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:≤20mΩ  
 接触电阻: ≤20mΩ  
 After environmental testing:≤30mΩ  
 环境测试后: ≤30兆欧  
 Operating Temperature:-40℃ to +105℃  
 工作温度: -40℃至 +105℃

**X9555WRX-2xXXA-PTV01XX**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- 1.Series No
- 2.Category:W-WAFER
- 3.Welding Board Angle:R-Right Angle 90°
- 4.Welding Way:Blank-DIP
- 5.Row No-Pin No:2xXX-2x06P-2x64P
- 6.Plug the Pin&Special NO:A-Ejector Header
- 7.Material:PT-PBT 94V-0
- 8.Plating Category:V01-All Gold Flash
- 9.Color:Blank-Natural Color

| poles | Dimensions(mm) |       | poles | Dimensions(mm) |        |
|-------|----------------|-------|-------|----------------|--------|
|       | A              | B     |       | A              | B      |
| 2x06  | 5.08           | 26.82 | 2x26  | 30.48          | 52.22  |
| 2x08  | 7.60           | 29.36 | 2x30  | 35.56          | 57.30  |
| 2x10  | 10.16          | 31.90 | 2x34  | 40.64          | 62.38  |
| 2x14  | 15.24          | 36.98 | 2x40  | 48.26          | 70.00  |
| 2x16  | 17.78          | 39.52 | 2x50  | 60.96          | 82.70  |
| 2x20  | 22.86          | 44.60 | 2x60  | 73.66          | 95.40  |
| 2x24  | 27.94          | 49.68 | 2x64  | 78.74          | 100.48 |

|                     |              |               |             |                       |
|---------------------|--------------|---------------|-------------|-----------------------|
| X9555WR-2xXXA-PTV01 | PBT UL 94V-0 | Brass         | Gold-Flash  | X9555H                |
| PART NO             | Material     | Material(pin) | Finish(Pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司

|      |       |
|------|-------|
| 生    | 日期    |
| 效    |       |
| 效    |       |
| 效    |       |
| MARK | 文件工程章 |

|                        |         |
|------------------------|---------|
| units:                 | mm      |
| tolerance:             |         |
| X.X                    | ±0.2mm  |
| X.XX                   | ±0.1mm  |
| X.XXX                  | ±0.05mm |
| UNSPECIFIED TOLERANCES |         |

|                                       |      |             |
|---------------------------------------|------|-------------|
| DSND                                  | DATE | SCALE: N/A  |
| DWN                                   | DATE | VIEW:       |
| CHKD                                  | DATE | UNIT: mm/in |
| APPD                                  | DATE | SIZE: A4    |
| XKB INDUSTRIAL PRECISION CO., LIMITED |      |             |

|             |                               |          |
|-------------|-------------------------------|----------|
| MODEL TYPE: | Wire to board connector       |          |
| PART NO.:   | 2.54mm Crimp Style Connectors |          |
| DWG NO.:    | X9555WR-2xXXA-PTV01           |          |
| WEIGHT      | SHEET                         | REVISION |
| 1.0g        | 1/1                           | A0       |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [I/O Connectors](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[571763P](#) [61-168618-12P](#) [D20419-211](#) [72.250.1628.2](#) [72.250.2428.2](#) [76.350.0729.0](#) [76871-1403](#) [PCR-E36PM](#) [PCS-XE26LKA](#) [PCS-XES68MS+](#) [G38A71314B](#) [9776-18-6](#) [1571250010](#) [157-22500-3](#) [MS3471L14-19P L/C](#) [192991-0703](#) [91-644626-35P](#) [172501-6002](#) [FCN-260C008-A/L0](#) [FCN-260C024-AL0](#) [FCN-261Z008](#) [2000314-1](#) [200331-1](#) [PCS-E28FS+](#) [PCS-XE26SLFD+](#) [PCS-XE26SLFDT+](#) [G730VID08BDC24](#) [HDMR-29-01-S-SM-TR](#) [HDRA-E68W1LFDTC-SL+](#) [54182-0605](#) [UE86K842720321](#) [38113800006](#) [DP3AR020WQ1R200](#) [Z4.102.0680.0](#) [500-1040](#) [500-1052](#) [500-1054](#) [ZP-4008-66L](#) [10-565995-597N](#) [10-584459-12P](#) [5554841-1](#) [SM3106F14S-7S-LC](#) [SM3106R18-18S](#) [U90B3054061110](#) [U65-E04-4020](#) [ZPF000000000097891](#) [557-262M2-06C](#) [PCS-96LFD+](#) [60-042222-02S](#) [10099439-003C-TRLF](#)