



Specifications:

规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage:1500V AC/minute
 耐受电压: 1500V AC/分钟
 Temperature range:-25℃~+85℃
 温度范围: -25℃~+85℃
 Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ
 After environmental testing:≤30mΩ
 环境测试后: ≤30兆欧

X9555 W R X-2xXX X-6T V01 XX

- ① ②③④ ⑤ ⑥⑦ ⑧ ⑨

- 1.Series No
- 2.Category:W-wafer
- 3.Welding Board Angle:R-Right Angle 90°
- 4.Welding Way:Blank-DIP
- 5.Row No-Pin No:2xXX-2x02P~2x32P
- 6.Plug the Pin&Special No:
- 7.Material:6T-PA6T 94V-0
- 8.Planting Category:V01-All Gold Flash
V05-All 5u" Gold
- 9.Color:Blank-Natural Color

| poles | Dimensions(mm) | | poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B |
| 2x02 | 2.54 | 12.68 | 2x12 | 27.94 | 38.25 |
| 2x03 | 5.08 | 15.22 | 2x13 | 30.50 | 40.65 |
| 2x04 | 7.62 | 17.76 | 2x15 | 35.56 | 45.80 |
| 2x05 | 10.16 | 20.30 | 2x17 | 40.64 | 50.78 |
| 2x06 | 12.70 | 22.84 | 2x20 | 48.26 | 58.40 |
| 2x07 | 15.24 | 25.38 | 2x25 | 60.86 | 71.10 |
| 2x08 | 17.78 | 27.92 | 2x30 | 73.70 | 84.15 |
| 2x09 | 20.32 | 30.46 | 2x32 | 78.74 | 89.00 |
| 2x10 | 22.86 | 33.00 | | | |

| | | | | |
|--------------------|---------------|---------------|-------------|-----------------------|
| X9555WR-2xXX-6TV05 | PA6T UL 94V-0 | Brass | 5u"Gold | X9555H |
| X9555WR-2xXX-6TV01 | | | Gold-Flash | |
| PART NO | Material | Material(Pin) | Finish(Pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司
 Recommended PCB Layout
 General Tolerance±0.05

| | | | | | | |
|---|-------------|------|---------|----------|--|------------------------|
| 生 | 日期 | | | | | units: mm |
| ΔX | | | | | | tolerance: X.X ±0.2mm |
| ΔX | | | | | | X.XX ±0.1mm |
| ΔX | | | | | | X.XXX ±0.05mm |
| MARK | DESCRIPTION | DATE | REVISED | APPROVED | | UNSPECIFIED TOLERANCES |
| www.xk-dg.cn www.helloxkb.com www.helloxkb.cn | | | | | | |

| | | | |
|---------------------------------------|------|-------------|--|
| DSND | DATE | SCALE: N/A | MODEL TYPE: Wire to board connector |
| DWN | DATE | VIEW: | PART NO.: 2.54mm Crimp Style Connectors |
| CHKD | DATE | UNIT: mm/in | DWG NO.: X9555WR-2xXX-6TV01 |
| APPD | DATE | SIZE: A4 | WEIGHT: 1.0g |
| KKB INDUSTRIAL PRECISION CO., LIMITED | | | SHEET: 1/1 |
| | | | REVISION: A0 |

文件工程章

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)