



PIN 数	A		B		C		D		E		F
	1.25	6.10	7.45	2.95	3.75	2.55	3.80	5.05	6.30		
2	1.25	6.10	7.45	2.95	3.75	2.55	3.80	5.05	6.30	21.25	
3	2.50	8.70	8.70	4.20	5.00	3.80	5.05	6.30	21.25	20.00	
4	3.75	9.95	9.95	5.45	6.25	5.05	6.30	21.25	20.00	18.75	
5	5.00	11.20	11.20	6.70	7.50	6.25	7.50	11.25	12.50	17.50	
6	6.25	12.45	12.45	7.95	8.75	7.50	8.75	11.25	12.50	16.25	
7	7.50	13.70	13.70	9.20	10.00	8.75	10.00	11.25	12.50	15.00	
8	8.75	14.95	14.95	10.45	11.25	10.00	11.25	12.50	13.75	13.75	
9	10.00	16.20	16.20	11.70	12.50	11.25	12.50	13.75	15.00	12.50	
10	11.25	17.45	17.45	12.95	13.75	12.50	13.75	15.00	16.25	11.25	
11	12.50	18.70	18.70	14.20	15.00	13.75	15.00	16.25	17.50	10.00	
12	13.75	19.95	19.95	15.45	16.25	15.00	16.25	17.50	18.75	8.75	
13	15.00	21.20	21.20	16.70	17.50	16.25	17.50	18.75	20.00	7.50	
14	16.25	22.45	22.45	17.95	18.75	17.50	18.75	20.00	21.25	6.25	
15	17.50	23.70	23.70	19.20	20.00	18.75	20.00	21.25	22.45	5.00	
16	18.75	24.95	24.95	20.45	21.25	20.00	21.25	22.45	23.70	3.75	

PART NO	X9862WVS-XXA-LPSN
Material	LCP UL 94V-0
Material(Pin)	Brass
Finish(Pin)	Tin-Plated
Material(Shell)	Brass
Finish(Shell)	Tin-Plated
Suitable XKB Terminal	X1255H

- ① Series No. X9862 W V S-XX A- LP SN XX
- ② Category: W-water
- ③ Welding Board Angle: V- Straight 180°
- ④ Welding Way: S-SMT
- ⑤ Row No.-Pin No.: XX-02P~30P
- ⑥ Plug the Pin & Special No.: A-With Lock
- ⑦ Material: LP-LCP 94V-0
- ⑧ Plating Category: SN-Bright tin plating
- ⑨ Color: Blank-Natural Color

- Specifications:
- Voltage rating: 200V AC / DC
 - Current rating: 1A AC / DC
 - Withstanding voltage: 500V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance: ≥100MΩ
 - Contact resistance: ≤40mΩ
 - After environmental testing: ≤50mΩ

REVISIONS		UNSPECIFIED TOLERANCES		APPROVED		REVISED		DATE		DESCRIPTION		MARK	
X9862WVS-XXA-LPSN		±0.2		±0.4		±0.3		±0.4		±0.4		△ X	
X9862WVS-XXA-LPSN		±0.2		±0.4		±0.3		±0.4		±0.4		△ X	
X9862WVS-XXA-LPSN		±0.2		±0.4		±0.3		±0.4		±0.4		△ X	
X9862WVS-XXA-LPSN		±0.2		±0.4		±0.3		±0.4		±0.4		△ X	

DATE	SCALE: N/A	MODEL TYPE:	X9862WVS-XXA-LPSN
DATE	VIEW:	PART NO.:	1.25mm Crimp Style Connectors
DATE	UNIT: mm	DWG NO.:	
DATE	SIZE: A4	REVISION	1/1
DATE	WEIGHT	SHEET	1.0g

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)