



1.8 ± 0.2 5.1 ± 0.1





PCB LAYOT

FEATURES

- Light operating force.
- Long term low contact resistance.
 Momentary or latching operation.
 Short stroke 1.5mm to latch.

■ SPECIFIC ATIONS

1.ELECTRICAL

Contact rating	0.1 A, 30VDC				
 Contact resistance 	50mWMax.				
● Insulation resistance	100 MWMin. at 250 VDC				
Dielectric strength	250VAC Min. for 60 sec.				

2.MECHANICAL AND ENVIRONMENTAL

Temperature rating	Operating: -15°C to +55°C Storage: -25°C to +65°C
Operation force	$250 \pm 50 \mathrm{gf}$
● Stroke	Lock Stroke: 1.5±0.2mm Full Stroke: 2.0±0.2mm
Operating life	full load: 1x10 ⁴ cycles no load: 1x10 ⁵ cycles
Contact form	DPDT

PAPT NO	XKB5858-X-F-75		
OPERATION .	W:NO LOCK Z:LOCK		

7	Contact	 .	2	Phosphor bronze	Plating silvering	
6	Terminal	ninal —		Brass	Plating silvering	
(5)	Spring		1	Sus	Natural	`
4	Base		1	Ppa		
(S)	Crochet Needle		1	Sus	Natural	
0	Cover	er <u> </u>		Ppa		
1	Keystake		1	Ppa		
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

CIRCUIT DIAGRAN

					ANGLAR	±5°			
ΔX					X.X	±0.2mm			
ΔX					X.XX	±0.1mm			
ΔX					X.XXX	±0.05mm			
MARK	DESCRIPTION	DATE	REVISED	APPROVED					
	REVISIONS UNSPECIFIED TOLERANCES								
	www.xk-dg.cn www.helloxkb.com www.helloxkb.cn								

DSND		DATE		SCALE: N/A	MODEL TYPE: KEY SW		NITCH
DWN		DATE		VIEW 🔷 🚭	PART NO.:	IXET O	7111011
CHKD		DATE		UNIT: mm	DIMO NO		
APPD		DATE		SIZE: A4	DWG NO.: XKB5858-X-F-7		
YKB	INDUSTRIAL F	LIMITED	WEIGHT	SHEET	REVISION		
	HADOS HVIAL F	1.0g	1/1	A0			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by XKB manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL

FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N
B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511

1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184

RELBARF6X10(PLASTIC) 13435AG