

## **FEATURES**

- Light operating force.
- Long term low contact resistance.
  Momentary or latching operation.
- Short stroke 1.5mm to latch.

### **■ SPECIFIC ATIONS**

#### 1.ELECTRICAL

<ul><li>Contact rating</li></ul>	0.1 A, 30VDC
<ul> <li>Contact resistance</li> </ul>	50mWMax.
■ Insulation resistance	100 MWMin. at 250 VDC
Dielectric strength	250VAC Min. for 60 sec.

#### 2.MECHANICAL AND ENVIRONMENTAL

Temperature rating	Operating: -15°C to +55°C Storage: -25°C to +65°C
<ul><li>Operation force</li></ul>	$250 \pm 50 \mathrm{gf}$
● Stroke	Lock Stroke: 1.5±0.2mm Full Stroke: 2.0±0.2mm
Operating life	full load: 1x10 <sup>4</sup> cycles no load: 1x10 <sup>5</sup> cycles
Contact form	DPDT

PAPT NO	XKB5858-X-F
OPERATION	W:NO LOCK Z:LOCK

7	Contact	—	2	Phosphor bronze	Plating silvering	
6	Terminal		6	Brass	Plating silvering	
(5)	Spring		1	Sus	Natural	
4	Base		1	Ppa		
3	Crochet Needle		1	Sus	Natural	
2	Cover		1	Ppa		
1	Keystake		1	Ppa		
ITEM	PAPT NAMF	TER,NO	QTY	MATER <b>I</b> AL	FINISHING	REMARK

C1RCU1T D1AGRAN						DSND		DATE		SCALE: N/A	MODEL TYPE: KEY SWITCH				
					ANGLAR	±5°	DWN		DATE		VIEW:	DART NO		VVIIOII	
ΔX					X.X	±0.2mm					+ -	I FAIRT NO.	•		
ΔΧ					X.XX	±0.1mm	CHKD		DATE		UNIT: mm				
ΔX					X.XXX	±0.05mm	<del></del>					DWG NO.:	VVDEO	50 V F	
MARK	DESCRIPTION	DATE	REVISED	APPROVED			APPD		DATE		SIZE: A4		O: XKB5858-X-F		
REVISIONS					UNSPECIFIED :	TOLERANCES	VICE INDUCTRIAL PRECICION CO. LIMITER			LIMITED	WEIGHT	SHEET	REVISION		
	www.xk-dg.cn www.helloxkb.com www.helloxkb.cn						XKB INDUSTRIAL PRECISION CO.,LIMITED				1.0g	1/1	A0		

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by XKB manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL

FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N
B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511

1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184

RELBARF6X10(PLASTIC) 13435AG