


RECOMMENDED PCB LAYOUT
GENERAL TOLERANCE ±0.05

Main technical performance	
Rated electrical load	DC 30V 5A
Insulation resistance	≥100MΩ(DC250V)
Pressure resistance	AC500V(50Hz)/MIN
Insertion force	3-25N
Operating temperature range	-40C°~+85C°
service life	5000cycles



SCHMATIC

7	圆针	1	黄铜	镀银
6	前盖	1	磷铜	镀镍
5	盖脚	1	磷铜	镀镍
4	平片	1	黄铜	镀银
3	插片	1	黄铜	镀银
2	弹片	1	磷铜	镀银
1	底座	1	PA9T(黑色)	
序号	名称	数量	材料	备注

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: DC SOCKET
			PAR DC-510-ACL200-H072
			DWN Lucas
			CHKD Ethan
DECIMALS:	ANGLES:	APVD Jacob	
X.:±0.20	X':±1°	SCALE:1:1 UNIT:MM	
X.X:±0.10	X.X':±0.5°	SIZE:A4	
X.XX:±0.05		CUSTOMER COPY	SHEET:1F1 REV:A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [XUNPU](#) manufacturer:

Other Similar products are found below :

[KLDX-SMT-0202-BPTR](#) [171-0722-E](#) [K596](#) [KLD-0201-BC](#) [4C6831AX](#) [10073976-112LF](#) [LCB60PW-M](#) [LCB30PW-M](#) [LCB60PB-M](#)
[LCC30PB-M](#) [LCB50PW-M](#) [LCB50-M](#) [LCB60-F](#) [LCC30-M](#) [LCB40PW-M](#) [LCC30PW-M](#) [LCB50-F](#) [LCB40-F](#) [LCB30-F](#) [LCC40-M](#)
[LCC40PB-M](#) [LCB40PB-M](#) [LCC40-F](#) [LCB60-M](#) [LCC40PW-M](#) [LCB50PB-M](#) [DC-002-100](#) [DC-031A-130](#) [DC-031A-100](#) [DC-003A-130](#)
[DC-045-130](#) [DC-192-130](#) [DC-033-130](#) [DC-011-100](#) [DC-002F-130](#) [DC-002-130](#) [DB-14-2F](#) [DC-183B](#) [DC-060-04A](#) [DC-099-200](#) [DC-015-](#)
[250-A](#) [DC-016-200-A](#) [DC-005A-200](#) [DC-044A-200](#) [DC-088-200](#) [DC-022A-200](#) [DC-038-150](#) [DC-012A-250](#) [DC-005C-130](#) [DC-012A-200](#)