


[P.C.B.LAYOUT]



[Schematic]


NOTES:

- 1.Specification:
- 1>.Operation force: 1000gf Max.
  - 2>.Operation Temperature: -30℃ to +85℃.
  - 3>.Storage Temperature: -40℃ to +85℃.
  - 4>.Mechanical Life: 3000 cycles operations.
  - 5>.Resistance to Soldering: 260±5℃ for 3-5 Seconds.

- 2.PLATING:
- 1>.GOLD flash 1u”(min) SOLDERTAIL,
  - 3u” GOLD PLATING ON THE CONTACT AREA.

- 3.ELECTRICAL:
- 1>.Non-switch Rating:100mA at 50V DC.
  - 2>.Switching Rating: 25mA at 24V DC.
  - 3>.Contact Resistance: Inital 50mΩ Max.  
Contact Resistance: After life 100mΩ Max.
  - 4>.Insulation Resistance:100MΩ Min at 500VDC.
  - 5>.Dielectric Strength: 500V AC for 60seconds.
  - 6>.Switch Capacitance: 5PF Max at 1MHZ.

4.PART NUMBER DESCRIPTION:



5.PACKING:20pcs/Tube,1600pcs/Box.

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd		
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE:PRODUCT Family DSIC Series Pitch 2.54mm	
DECIMALS:	ANGLES:		PAR	DSIC-10-LS-GER
>0±0.05	>0°±0.5°		DWN	
>1±0.10	>5°±1.0°		CHKD	
>10±0.30		APVD		
		SCALE:1:1	UNIT:MM	
		CUSTOMER COPY	SIZE:A4	SHEET:1F1
				REV:A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DIP Switches/SIP Switches](#) category:*

*Click to view products by [XUNPU](#) manufacturer:*

Other Similar products are found below :

[79B10T](#) [8136-475G4T](#) [G7G-1A2-CB-DC12](#) [DRS4016](#) [1825444-1](#) [193005MS](#) [195010MS](#) [200183](#) [206002](#) [208004](#) [208007ST](#) [208008](#)  
[25.350.0653.0](#) [SDA10H1BDA](#) [97R06ST](#) [A2C-2A5](#) [1825444-7](#) [ADE12S04](#) [206005RAS](#) [209005LPST](#) [2-1825058-8](#) [219002LPST](#)  
[219002MSTJRF](#) [219012MST](#) [25.352.0353.0](#) [CXDRIVEV2X](#) [LA2-002-DC24](#) [DSR02T](#) [193004MS](#) [E2FMX2D1M1TGJ03M](#) [NDI10H](#) [219-](#)  
[9MSTP](#) [219008LPSTR](#) [EPM02FV](#) [206010RAST](#) [76SB05](#) [TD06H0SK1](#) [Z7.255.9027.0](#) [1-1825058-3](#) [1825428-4](#) [219-10LPSTF](#)  
[E3ZG6111D03M](#) [G4D212PUSTV2DC5](#) [HARW0002](#) [EPG301BT06](#) [1-1825058-6](#) [E3TSL23M5J03M](#) [Y5795](#) [7R0060](#) [HARW0001](#)