



技术指标:

1. 温度范围:  $-25^{\circ}\text{C}\sim 85^{\circ}\text{C}$ .
2. 额定电压: 250V AC,DC.
3. 耐压: 1500V AC/minute.
4. 接触电阻:  $\leq 20\text{m}\Omega$ .
5. 绝缘电阻:  $\geq 1000\text{M}\Omega$ .
6. 额定电流: 5A AC,DC.

型号	CKT	A	B
WAFER-WBM4.2-02PJK-GB	2*1	0.00	5.50
WAFER-WBM4.2-04PJK-GB	2*2	4.20	9.70
WAFER-WBM4.2-06PJK-GB	2*3	8.40	13.90
WAFER-WBM4.2-08PJK-GB	2*4	12.60	18.10
WAFER-WBM4.2-10PJK-GB	2*5	16.80	22.30
WAFER-WBM4.2-12PJK-GB	2*6	21.00	26.50
WAFER-WBM4.2-14PJK-GB	2*7	25.20	30.70
WAFER-WBM4.2-16PJK-GB	2*8	29.40	34.90
WAFER-WBM4.2-18PJK-GB	2*9	33.40	39.10
WAFER-WBM4.2-20PJK-GB	2*10	37.80	43.30
WAFER-WBM4.2-22PJK-GB	2*11	42.00	47.50
WAFER-WBM4.2-24PJK-GB	2*12	46.20	51.70

MANUFACTURE DWG			 东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: WBM4.2MM HOUSING	
DECIMALS:	ANGLES:	PAR	WAFER-WBM4.2-NPJK-GB	
X.X±0.30	X.*±5'	DWN		
X.XX±0.25	X.X'±1'	CHKD		
X.XXX±0.15		APVD		
CUSTOMER COPY		SCALE:A	UNIT:MM	
		SIZE:A4	SHEET:1F1	REV:A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XUNPU](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)