



| Part No | Pin | A | B | C |
|--------------------|-----|-------|-------|-------|
| WAFER-XH2.54-2PWB | 2 | 2.50 | 10.00 | 8.30 |
| WAFER-XH2.54-3PWB | 3 | 5.00 | 12.50 | 10.80 |
| WAFER-XH2.54-4PWB | 4 | 7.50 | 15.00 | 13.30 |
| WAFER-XH2.54-5PWB | 5 | 10.00 | 17.50 | 15.80 |
| WAFER-XH2.54-6PWB | 6 | 12.50 | 20.00 | 18.30 |
| WAFER-XH2.54-7PWB | 7 | 15.00 | 22.50 | 20.80 |
| WAFER-XH2.54-8PWB | 8 | 17.50 | 25.00 | 23.30 |
| WAFER-XH2.54-9PWB | 9 | 20.00 | 27.50 | 25.80 |
| WAFER-XH2.54-10PWB | 10 | 22.50 | 30.00 | 28.30 |
| WAFER-XH2.54-11PWB | 11 | 25.00 | 32.50 | 30.80 |
| WAFER-XH2.54-12PWB | 12 | 27.50 | 35.00 | 33.30 |
| WAFER-XH2.54-13PWB | 13 | 30.00 | 37.50 | 35.80 |
| WAFER-XH2.54-14PWB | 14 | 32.50 | 40.00 | 38.30 |
| WAFER-XH2.54-15PWB | 15 | 35.00 | 42.50 | 40.80 |
| WAFER-XH2.54-16PWB | 16 | 37.50 | 45.00 | 43.30 |

NOTES:

- 1.BASE: LCP
- 2.PIN: Brass
- 3.Solder Tab: Brass

SPECIFICATIONS:

- 1.Spacing: 2.5
- 2.Voltage Rating: 250V AC DC
- 3.Current Rating: 3A AC DC
- 4.Insulation Resistance: 800MΩ Min
- 5.Contact Resistance: 20mΩ Max
- 6.Withstanding voltage: 500V AC 1/Minute
- 7.Temperatuer Range: -25℃ ~+ 85℃

| | | | | |
|---------------------------------------|-----------|---|---|---|
| MANUFACTURE DWG | |  |  东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd | |
| UNLESS OTHERWISE SPECIFIED TOLERANCES | | | TITLE: WAFER 2.5 贴片 | |
| DECIMALS: | ANGLES: | PAR | WAFER-XH2.54-NPWB | |
| X.:±0.2 | X'.:±5° | DWN | | |
| .X:±0.1 | X.X':±3° | CHKD | | |
| .XX:±0.05 | X.XX':±1° | APVD | | |
| CUSTOMER COPY | | SCALE1:1 | UNIT:MM |  |
| | | SIZE:A4 | SHEET:1F1 | REV:A |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XUNPU](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)