





REV.	Q'TY	ECN. NO.	APR.	DATE

SPECIFICATIONS

Current Rating: 1.0 Amps
 Withstanding Voltage: AC 500V
 Insulation Resistance: 1000MΩ Min
 Contact Resistance: 20mΩ Max
 Operation Temperature: -40°to+105°
 Insulator Material: Polyester(UL94V-0)
 Contact Material: Phosphor bronze
 Standard: PA6T
 Contact Plating: Gold Flash
 Max.Processing Temp: 240°C for30-60seconds
 (260°C for5seconds)



RECOMMEND P.C.B LAYOUT
 PCB TOLERANCE:±0.05 (TOP VIEW)

Part No	Pin	A	B	Part No	Pin	A	B	Part No	Pin	A	B	Part No	Pin	A	B
PM1.27-US2S-1A	1	-	-	PM1.27-US2S-11A	11	12.70	13.97	PM1.27-US2S-21A	21	25.40	26.67	PM1.27-US2S-31A	31	38.10	39.37
PM1.27-US2S-2A	2	1.27	2.54	PM1.27-US2S-12A	12	13.97	15.24	PM1.27-US2S-22A	22	26.67	27.94	PM1.27-US2S-32A	32	39.37	40.64
PM1.27-US2S-3A	3	2.54	3.81	PM1.27-US2S-13A	13	15.24	16.51	PM1.27-US2S-23A	23	27.94	29.21	PM1.27-US2S-33A	33	40.64	41.91
PM1.27-US2S-4A	4	3.81	5.08	PM1.27-US2S-14A	14	16.51	17.78	PM1.27-US2S-24A	24	29.21	30.48	PM1.27-US2S-34A	34	41.91	43.18
PM1.27-US2S-5A	5	5.08	6.35	PM1.27-US2S-15A	15	17.78	19.05	PM1.27-US2S-25A	25	30.48	31.75	PM1.27-US2S-35A	35	43.18	44.45
PM1.27-US2S-6A	6	6.35	7.62	PM1.27-US2S-16A	16	19.05	20.32	PM1.27-US2S-26A	26	31.75	33.02	PM1.27-US2S-36A	36	44.45	45.72
PM1.27-US2S-7A	7	7.62	8.89	PM1.27-US2S-17A	17	20.32	21.59	PM1.27-US2S-27A	27	33.02	34.29	PM1.27-US2S-37A	37	45.72	46.99
PM1.27-US2S-8A	8	8.89	10.16	PM1.27-US2S-18A	18	21.59	22.86	PM1.27-US2S-28A	28	34.29	35.56	PM1.27-US2S-38A	38	46.99	48.26
PM1.27-US2S-9A	9	10.16	11.43	PM1.27-US2S-19A	19	22.86	24.13	PM1.27-US2S-29A	29	35.56	36.83	PM1.27-US2S-39A	39	48.26	49.53
PM1.27-US2S-10A	10	11.43	12.70	PM1.27-US2S-20A	20	24.13	25.40	PM1.27-US2S-30A	30	36.83	38.10	PM1.27-US2S-40A	40	49.53	50.80
				PM1.27-US2S-21A	21	25.40	26.67	PM1.27-US2S-31A	31	38.10	39.37	PM1.27-US2S-41A	41	50.80	52.07
				PM1.27-US2S-22A	22	26.67	27.94	PM1.27-US2S-32A	32	39.37	40.64	PM1.27-US2S-42A	42	52.07	53.34
				PM1.27-US2S-23A	23	27.94	29.21	PM1.27-US2S-33A	33	40.64	41.91	PM1.27-US2S-43A	43	53.34	54.61
				PM1.27-US2S-24A	24	29.21	30.48	PM1.27-US2S-34A	34	41.91	43.18	PM1.27-US2S-44A	44	54.61	55.88
				PM1.27-US2S-25A	25	30.48	31.75	PM1.27-US2S-35A	35	43.18	44.45	PM1.27-US2S-45A	45	55.88	57.15
				PM1.27-US2S-26A	26	31.75	33.02	PM1.27-US2S-36A	36	44.45	45.72	PM1.27-US2S-46A	46	57.15	58.42
				PM1.27-US2S-27A	27	33.02	34.29	PM1.27-US2S-37A	37	45.72	46.99	PM1.27-US2S-47A	47	58.42	59.69
				PM1.27-US2S-28A	28	34.29	35.56	PM1.27-US2S-38A	38	46.99	48.26	PM1.27-US2S-48A	48	59.69	60.96
				PM1.27-US2S-29A	29	35.56	36.83	PM1.27-US2S-39A	39	48.26	49.53	PM1.27-US2S-49A	49	60.96	62.23
				PM1.27-US2S-30A	30	36.83	38.10	PM1.27-US2S-40A	40	49.53	50.80	PM1.27-US2S-50A	50	62.23	63.50

DIMENSION IN mm		厦门市辛译精密电子有限公司 Xiamen XinYi Xyconn Electronics Co.,Ltd	
TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X±0.35	X.*± 5°	APR. Alex	TITLE: 1.27PM H4.3 2xNPin SMT U# PC4.8 PB4.6 6T
.XX±0.25	.X.*± 3°	CHK. Jack	DWG NO. PM1.27-US2S-NA
.XXX±0.15	.XX.*± 1°	DRA. Can	PROJ. CUSTOMER DRAWING
			SIZE A4 SCALE 1:1 SHEET 1/1 REV. A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XYECONN](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-](#)
[5028](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)