


## Wirewound Resistors

# General Type

## Normal & Miniature Style [ KNP Series ]



### INTRODUCTION


The resistor element is a resistive wire which is wound in a single layer on a ceramic rod, with tinned connecting wires of electrolytic copper welded to the end-caps. The ends of the resistive wire are connected to the caps by welding. The resistors are coated with layers of green color flame-proof lacquer.

### FEATURES

Power Rating	1/4W, 1/2W, 1W, 2W, 3W, 4W, 5W, 7W
Resistance Tolerance	±1%, ±5%
T.C.R.	±300ppm/°C
Flameproof Multi-layer Coating Meets	UL-94V-0
Flameproof Feature Meets Overload Test	UL-1412


### DERATING CURVE

For resistors operated in ambient temperatures above 40°C, power rating must be derated in accordance with the curve below.



### DIMENSIONS

Unit: mm



STYLE		DIMENSION			
Normal	Miniature	L	øD	H	ød
KNP-25	KNP50S	6.3±0.5	2.5±0.3	28±2.0	0.55±0.05
KNP-50	KNP1WS	9.0±0.5	3.5±0.3	26±2.0	0.55±0.05
KNP100	KNP2WS KNP3SS	11.5±1.0	4.6±0.5	35±2.0	0.8±0.05
KNP200	KNP3WS	15.5±1.0	5.2±0.5	33±2.0	0.8±0.05
KNP300	KNP5WS	17.5±1.0	6.2±0.5	32±2.0	0.8±0.05
KNP400					
KNP500	KNP7WS	24.5±1.0	8.2±0.5	38±2.0	0.8±0.05
KNP600					
KNP700	-	24.5±1.0	8.2±0.5	38±2.0	0.8±0.05

Note: KNP1WS ( for MBType ) ød = 0.8±0.05 mm

## ELECTRICAL CHARACTERISTICS

### NORMAL STYLE

STYLE	KNP-25	KNP-50	KNP100	KNP200	KNP300	KNP400	KNP500	KNP600	KNP700
Power Rating at 40°C					3W	4W	5W	6W	7W
Power Rating at 70°C	1/4W	1/2W	1W	2W					
Maximum working voltage	$\sqrt{P \times R}$								
Voltage Proof on Insulation	250V	300V	400V						
Resistance Range ( $\pm 1\%$ )	0.1 $\Omega$ - 150 $\Omega$	0.1 $\Omega$ - 750 $\Omega$	0.1 $\Omega$ - 1.5K $\Omega$	0.1 $\Omega$ - 2.4K $\Omega$	0.1 $\Omega$ - 3.3K $\Omega$		0.1 $\Omega$ - 6.2K $\Omega$		
Resistance Range ( $\pm 5\%$ )	0.1 $\Omega$ - 200 $\Omega$	0.1 $\Omega$ - 800 $\Omega$	0.1 $\Omega$ - 2.2K $\Omega$	0.1 $\Omega$ - 2.7K $\Omega$	0.1 $\Omega$ - 3.9K $\Omega$		0.1 $\Omega$ - 6.8K $\Omega$		
Operating Temp. Range	-40°C to +200°C								
Temperature Coefficient	$\pm 300\text{ppm}/^\circ\text{C}$								

Note: Special value is available on request

### MINIATURE STYLE

STYLE	KNP50S	KNP1WS	KNP2WS	KNP3SS	KNP3WS	KNP5WS	KNP7WS
Power Rating at 40°C						5W	7W
Power Rating at 70°C	1/2W	1W	2W	3W			
Maximum working voltage	$\sqrt{P \times R}$						
Voltage Proof on Insulation	200V	300V	400V				
Resistance Range ( $\pm 1\%$ )	0.1 $\Omega$ - 150 $\Omega$	0.1 $\Omega$ - 750 $\Omega$	0.1 $\Omega$ - 1.5K $\Omega$		0.1 $\Omega$ - 2.4K $\Omega$	0.1 $\Omega$ - 3.3K $\Omega$	
Resistance Range ( $\pm 5\%$ )	0.1 $\Omega$ - 200 $\Omega$	0.1 $\Omega$ - 800 $\Omega$	0.1 $\Omega$ - 2.2K $\Omega$		0.1 $\Omega$ - 2.7K $\Omega$	0.1 $\Omega$ - 3.9K $\Omega$	
Operating Temp. Range	-40°C to +200°C						
Temperature Coefficient	$\pm 300\text{ppm}/^\circ\text{C}$						

Note: Special value is available on request

## ENVIRONMENTAL CHARACTERISTICS

PERFORMANCE TEST	TEST METHOD		APPRAISE
Short Time Overload	IEC 60115-1 4.13	10 times rated power for 5 Sec.	$\pm 2.0\% + 0.05\Omega$
Voltage Proof on Insulation	IEC 60115-1 4.7	In V-Block for 60 sec., test voltage as above table	No Breakdown
Temperature Coefficient	IEC 60115-1 4.8	Between -40°C to +155°C	By type
Insulation Resistance	IEC 60115-1 4.6	in V-block for 60 Sec.	>100M $\Omega$
Solderability	IEC 60115-1 4.17	235 $\pm 5^\circ\text{C}$ for 3 $\pm 0.5$ Sec	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5 $\pm 0.5$ Min. with ultrasonic	No deterioration of coatings and markings
Robustness of Terminations	IEC 60115-1 4.16	Direct load for 10 Sec. in the direction of the terminal leads	$\geq 2.5\text{kg}$ (24.5N)
Damp Heat Steady State	IEC 60115-1 4.24	40 $\pm 2^\circ\text{C}$ , 90-95% RH for 56 days, loaded with 0.1 times RCWV	$\pm 5.0\% + 0.05\Omega$
Endurance at 70°C	IEC 60115-1 4.25	70 $\pm 2^\circ\text{C}$ at RCWV (or $U_{\text{max}}$ , whichever less) for 1,000 Hr. (1.5Hr:on, 0.5Hr: Off)	$\pm 5.0\% + 0.05\Omega$
Temperature Cycling	IEC 60115-1 4.19	-55°C $\Rightarrow$ Room Temp. $\Rightarrow$ +155°C $\Rightarrow$ Room Temp. (5 cycles)	$\pm 1.0\% + 0.05\Omega$
Resistance to Soldering Heat	IEC 60115-1 4.18	260 $\pm 3^\circ\text{C}$ for 10 $\pm 1$ Sec., immersed to a point 3 $\pm 0.5\text{mm}$ from the body	$\pm 1.0\% + 0.05\Omega$
Accidental Overload Test	IEC 60115-1 4.26	4 times RCWV for 1 Min.	No evidence of flaming or arcing

Note: Rated Continuous Working Voltage (RCWV) =  $\sqrt{\text{Power Rating} \times \text{Resistance Value}}$  or Max. working voltage listed above, whichever less.

Revision: 2020

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Wirewound Resistors - Through Hole](#) category:*

*Click to view products by [Yageo](#) manufacturer:*

Other Similar products are found below :

[75822-2K4](#) [G05C7R000HB1223](#) [G22041431007J2C000](#) [PW10-39R-5%](#) [AC04000008209JAC00](#) [C142K2JL](#) [CA00021R000JE14](#)  
[RW35V100](#) [RWR81SR427DRB12](#) [93J62RE](#) [25J39K](#) [CP0005330R0JE3191](#) [CPCC03R5000JB31](#) [CPCP10500R0JE32](#) [CPCP106K800JE32](#)  
[CPW152K500JE313](#) [C1010RJL](#) [CA000210R00JE14](#) [RS02B887R0FE73](#) [NS02B20R00JE73](#) [CPCC03R2000JB31](#) [CPW103K300JE143](#)  
[CPW202R000JB14](#) [WA85Z-47RJI](#) [W31-R47JA1](#) [W31-R047JA1](#) [VP25K-120](#) [VC3D900](#) [65888-3R3](#) [RWR80S6R04FRB12](#)  
[CP000533R00JE66](#) [RWR80S4R64FRB12](#) [SQM500JB-200R](#) [75822-10R](#) [WHS201-68RJA25](#) [W31-1K2JA1](#) [25W110-BULK](#) [25W156](#)  
[25W239](#) [25W3D3-BULK](#) [RW33V180](#) [135-R47-JBW](#) [25WD75-BULK](#) [5W018-BULK](#) [5W115-BULK](#) [10W068-BULK](#) [C1500K12R](#) [PW5-](#)  
[750-JBW](#) [85J5K1](#) [PAC500002507FAC000](#)