

Coating Type

Normal Style [ZOR Series]



INTRODUCTION

- Ideal for automatic insertion or Cut and Form
- Available in Tape/Reel, Tape/Box and Bulk
- Products meet EU-RoHS requirements


SPECIFICATIONS

Power Rating Maximum Resistance		$\frac{\text{1/6W,1/4W}}{\text{10m}\Omega \text{ or less}}$	
Wet	ΙΟΟΜΩ		
	Atmospheric	500V RMS	
Min. Dielectric Withstanding Voltage	Reduced	325V RMS	
Insulation Flammability		Resistor insulation is self extinguishing within 10 Sec. after externally applied flame is removed	
Current Rating		10 AMPS at 70°C for ZOR-25 8 AMPS at 70°C for ZOR-12	

DFRATING CURVE

For resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with the curve below.


Rated Load (%)



Ambient Temperature (°C)

DIMENSIONS

l	Jn	it:	m	m



STYLE	DIMENSION						
Normal	L	øD	н	ød			
ZOR-12	3.3±0.4	1.8±0.3	28±2.0	0.45±0.05			
ZOR-25	6.3±0.5	2.3±0.3	28±2.0	0.55±0.05			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Metal Film Resistors - Through Hole category:

Click to view products by Yageo manufacturer:

Other Similar products are found below:

MF2S-6K8JI GP55S-1002-FTW GP55S-1004-FTW GP55S-4753-FTW QW210 RCFH-0.5-5TA RCFH-100-5TA RCFH-10-5TA RCFH-110-5TA RCFH-11M-5TA RCFH-12K-5TA RCFH-130K-5TA RCFH-13-5TA RCFH-13K-5TA RCFH-13M-5TA RCFH-150K-5TA RCFH-15-5TA RCFH-160-5TA RCFH-160K-5TA RCFH-16-5TA RCFH-180K-5TA RCFH-18K-5TA RCFH-1M-5TA RCFH-200-5TA RCFH-200K-5TA RCFH-20K-5TA RCFH-220K-5TA RCFH-220K-5TA RCFH-22K-5TA RCFH-22M-5TA RCFH-240K-5TA RCFH-24K-5TA RCFH-2-5TA RCFH-27-5TA RCFH-27K-5TA RCFH-27K-5TA RCFH-330-5TA RCFH-33-5TA RCFH-33M-5TA RCFH-360-5TA RCFH-360K-5TA RCFH-3.6M-5TA RCFH-39-5TA RCFH-39K-5TA RCFH-3.9M-5TA RCFH-430-5TA RCFH-47K-5TA RCFH-510K-5TA RCFH-51-5TA