

Programmable Crystal Oscillator YSO160PR




Applications

- 10 GB Ethernet, SONET, SATA, SAS, Fibre Channel.

Features

- Freq. Range: 10MHz-250MHz.
- Ultra Small SMD seam sealed crystal oscillator units.

- Package Size: 3.2*2.5, 5.0*3.2, 7.0*5.0mm.
- High precision characteristic covering up to wide frequency range.



Specifications

Item / Type	SMD VCXO	CMOS
Output Frequency Range		10MHz to 250MHz, or specify
Supply Voltage		2.5V or 3.3V
Total Stability		±30ppm, ±50ppm or specify
Operating Temperature Range		-40~+85°C, or specify
Storage Temperature Range		-55~+125°C
Input Resistance		1Mohms Typ
Current Consumption		40mA Max
Output Load		15pF(max)
Voltage Vol (Max.) / Vol (Min.)		VOH = 90%Vdd/VOL = 10%Vdd
Duty Cycle		45~55%
Input Voltage		VIH=70% Vcc Min, VIL=30% Vdd Max.
Rise Time / Fall Time (20% to 80% Waveform)		4.0nsec (max.)
Start-up Time		10msec. (max.)
Aging		±3 ppm / year Max.
RMS Jitter [12 kHz ~ 20 MHz]		1.0pS Typ.

Pin Dimension

Pin	#1	#2	#3	#4	#5	#6
FUNCTION	OE	NC	GND	OUT	NC	VDD

Top View




Figure 1. Pin Assignments

Programmable Crystal Oscillator YSO160PR



Dimensions and Recommended land pattern

Package Size – Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)
<p>3.2*2.5mm</p> <p>Top View</p> <p>Bottom View</p> <p>Side View</p>	
<p>5.0*3.2mm</p> <p>Top View</p> <p>Bottom View</p> <p>Side View</p>	
<p>7.0*5.0mm</p> <p>Top View</p> <p>Bottom View</p> <p>Side View</p>	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Clock Oscillators](#) category:

Click to view products by [Yangxing](#) manufacturer:

Other Similar products are found below :

[F335-25](#) [F535L-33.333](#) [F535L-50](#) [NBXHBA019LN1TAG](#) [SiT1602BI-22-33E-50.000000E](#) [SIT8918AA-11-33S-50.000000G](#) [SM4420TEV-40.0M-T1K](#) [F335-24](#) [F335-40](#) [F535L-10](#) [F535L-12](#) [F535L-24](#) [F535L-27](#) [PE7744DW-100.0M](#) [ASF1-3.686MHZ-N-K-S](#) [ASV-4.000MHZ-LCS-T](#) [XO57CTECNA3M6864](#) [601251](#) [SiT8503AI-18-33E-0.200000X](#) [SIT9122AI2C233E300.000000X](#) [9120AC-2D2-33E212.500000](#) [9102AI-243N25E100.000000](#) [8208AC-82-18E-25.000000](#) [8008AI-72-XXE-24.545454E](#) [8004AC-13-33E-133.330000X](#) [AS-4.9152-16-SMD-TR](#) [ASFL1-48.000MHZ-LC-T](#) [632L3I004M00000](#) [SIT8920AM-31-33E-25.0000](#) [DSC1028DI2-019.2000](#) [9121AC-2C3-25E100.000000](#) [9102AI-233N33E100.000000X](#) [9102AI-233N25E200.000000](#) [9102AI-232H25S125.000000](#) [9102AI-133N25E200.000000](#) [9102AC-283N25E200.000000](#) [9001AC-33-33E1-30.000](#) [8103AC-13-33E-12.000000X](#) [3921AI-2CF-33NZ125.000000](#) [5730-1SF](#) [XUN736000.032768I](#) [ASV-25.000MHZ-ECS-50-T](#) [EC3925ETTTS-100.000M TR](#) [SIT1602BC-83-33E-10.000000Y](#) [8003AI-12-33S-40.000000Y](#) [1602BI-13-33S-19.200000E](#) [8208AI-2F-18E-25.000000X](#) [8103AI-83-33E-33.000000X](#) [8208AI-8F-33E-66.666666X](#) [NX7031E0125.000000](#)