

Programmable Crystal Oscillator YSO210PR




Applications

- 10 GB Ethernet, SONET, SATA, SAS, Fibre Channel

Features

- Wide Frequency Range: 10 ~ 1500MHz
- Output LVPECL or LVDS
- Package Size: 3.2*2.5, 5.0*3.2, 7.0*5.0mm
- Quartz Crystal Programmable Differential Oscillator



Specifications (规格参数)

Item/Type	LVPECL	LVDS	Remarks	
Output Frequency Range 额定频率范围	10MHZ ~ 1500MHZ			
Supply Voltage 电源电压	2.5V, 3.3V			
Total Stability 频率偏差	±25ppm, ±50ppm, or specify		Inclusive of Initial tolerance at 25°C, 1st year aging at 25°C, and variations over operating temperature	
Operating Temperature Range 工作温度	-40~+85°C, or specify			
Storage Temperature Range 储存温度	-55~+150°C			
Current Consumption 消耗电流	80mA Max	50mA Max	OE=VDD, LVPECL=(50)Ω or LVDS=(100)Ω	
Disable Current 禁用电流	16mA Typ.		OE=GND	
Output Voltage (LVPECL) 输出电压 (LVPECL)	VOH=VDD-1.03 Min	--	DC characteristics	
	VOL=VDD-1.6 Max	--		
Output Voltage (LVDS) 输出电压 (LVDS)	--	VOD=350mV	VOD1, VOD2	DC characteristics
	--	dVOD=50mV Max	dVOD= VOD1-VOD2	
	--	VOS= 1.25V	VOS1, VOS2	
	--	dVOS=50mV Max	dVOS= VOD1-VOD2	
Output Load Condition 输出负载	L_PECL=50Ω	--	Terminated to VDD-2.0V	
	--	L_LVDS=100Ω	Connected between OUT to OUT	
Input Voltage 输入电压	VIH=70% VDD Min, VIL=30%VDD Max		OE terminal	
Rise Time/Fall Time 上升沿/下降沿	1nS Max		LVPECL: Between 20% and 80% of (VOH-VOL), LVDS: Between 20% and 80% Differential Output peak to peak voltage	

Programmable Crystal Oscillator YSO210PR



Item/Type	LVPECL	LVDS	Remarks
Duty Cycle 占空比	45~55%		
Start-up time 启动时间	10mS		Time at Minimum Supply Voltage to be 0s
RMS Jitter [12 kHz ~ 20 MHz] 相位抖动	1.0ps Typ.		200MHZ ~ 800MHZ
	2.0ps Typ.		801MHZ ~ 1500MHZ
Aging 老化率	±3ppm		25°C First year, VDD=2.5V, 3.3V

Pin Dimension (脚位尺寸)

Pin	#1	#2	#3	#4	#5	#6
FUNCTION	OE	NC	GND	OUT+	OUT-	VDD





Figure 1. Pin Assignments

Notes: To maintain stable operation provide a 0.01uF to 0.1uF by-pass capacitor at a location as near as possible to the power source terminal of the crystal product (between VDD-GND).


Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)
<p>3.2*2.5mm</p>	
<p>5.0*3.2mm</p>	

Programmable Crystal Oscillator YSO210PR



Test Circuit (测试电路)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Clock Oscillators](#) category:

Click to view products by [Yangxing](#) manufacturer:

Other Similar products are found below :

[F335-25](#) [F535L-33.333](#) [F535L-50](#) [NBXHBA019LN1TAG](#) [SiT1602BI-22-33E-50.000000E](#) [SIT8918AA-11-33S-50.000000G](#) [SM4420TEV-40.0M-T1K](#) [F335-24](#) [F335-40](#) [F535L-10](#) [F535L-12](#) [F535L-24](#) [F535L-27](#) [PE7744DW-100.0M](#) [ASF1-3.686MHZ-N-K-S](#) [ASV-4.000MHZ-LCS-T](#) [XO57CTECNA3M6864](#) [601251](#) [SiT8503AI-18-33E-0.200000X](#) [SIT9122AI2C233E300.000000X](#) [9120AC-2D2-33E212.500000](#) [9102AI-243N25E100.000000](#) [8208AC-82-18E-25.000000](#) [8008AI-72-XXE-24.545454E](#) [8004AC-13-33E-133.330000X](#) [AS-4.9152-16-SMD-TR](#) [ASFL1-48.000MHZ-LC-T](#) [632L3I004M00000](#) [SIT8920AM-31-33E-25.0000](#) [DSC1028DI2-019.2000](#) [9121AC-2C3-25E100.000000](#) [9102AI-233N33E100.000000X](#) [9102AI-233N25E200.000000](#) [9102AI-232H25S125.000000](#) [9102AI-133N25E200.000000](#) [9102AC-283N25E200.000000](#) [9001AC-33-33E1-30.000](#) [8103AC-13-33E-12.000000X](#) [3921AI-2CF-33NZ125.000000](#) [5730-1SF](#) [XUN736000.032768I](#) [ASV-25.000MHZ-ECS-50-T](#) [EC3925ETTTS-100.000M TR](#) [SIT1602BC-83-33E-10.000000Y](#) [8003AI-12-33S-40.000000Y](#) [1602BI-13-33S-19.200000E](#) [8208AI-2F-18E-25.000000X](#) [8103AI-83-33E-33.000000X](#) [8208AI-8F-33E-66.666666X](#) [NX7031E0125.000000](#)