


■ N-Channel MOSFET




- 1. Gate
- 2. Source
- 3. Drain

■ Features

- $V_{DS} (V) = 30V$
- $I_D = 0.1 A$
- $R_{DS(ON)} < 8 \Omega (V_{GS} = 4V)$
- $R_{DS(ON)} < 13 \Omega (V_{GS} = 2.5V)$

■ Simplified outline(SOT-23)



■ Marking

| | |
|---------|----|
| Marking | KN |
|---------|----|

■ Absolute Maximum Ratings $T_a = 25^\circ C$

| Parameter | Symbol | Rating | Unit |
|-------------------------------|-----------|------------|------------|
| Drain-Source Voltage | V_{DS} | 30 | V |
| Gate-Source Voltage | V_{GS} | ± 20 | |
| Continuous Drain Current | I_D | 100 | mA |
| Pulsed Drain Current (Note.1) | I_{DM} | 400 | |
| Power Dissipation | P_D | 200 | mW |
| Junction Temperature | T_J | 150 | $^\circ C$ |
| Storage Temperature Range | T_{stg} | -55 to 150 | |

Note.1: $PW \leq 10\mu s$, Duty Cycle $\leq 1\%$

■ Electrical Characteristics $T_a = 25^\circ C$

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-----------------------------------|--------------|---|-----|-----|---------|----------|
| Drain-Source Breakdown Voltage | V_{DSS} | $I_D=250 \mu A, V_{GS}=0V$ | 30 | | | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS}=30V, V_{GS}=0V$ | | | 1 | μA |
| Gate-Body Leakage Current | I_{GSS} | $V_{DS}=0V, V_{GS}=\pm 20V$ | | | ± 1 | μA |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}=3V, I_D=0.1mA$ | 0.8 | | 1.5 | V |
| Static Drain-Source On-Resistance | $R_{DS(on)}$ | $V_{GS}=4V, I_D=10mA$ | | | 8 | Ω |
| | | $V_{GS}=2.5V, I_D=1mA$ | | | 13 | |
| Forward Transconductance | g_{FS} | $V_{DS}=3V, I_D=10mA$ | 20 | | | mS |
| Input Capacitance | C_{iss} | $V_{GS}=0V, V_{DS}=5V, f=1MHz$ | | 13 | | pF |
| Output Capacitance | C_{oss} | | | 9 | | |
| Reverse Transfer Capacitance | C_{rss} | | | 4 | | |
| Turn-On DelayTime | $t_{d(on)}$ | $V_{GS}=5V, V_{DS}=5V, I_D=10mA, R_L=500 \Omega, R_G=10 \Omega$ | | 15 | | ns |
| Turn-On Rise Time | t_r | | | 35 | | |
| Turn-Off DelayTime | $t_{d(off)}$ | | | 80 | | |
| Turn-Off Fall Time | t_f | | | 80 | | |

■ Typical Characteristics




Fig.1 Typical output characteristics




Fig.2 Typical transfer characteristics




Fig.3 Gate threshold voltage vs. channel temperature




Fig.4 Static drain-source on-state resistance vs. drain current (I)




Fig.5 Static drain-source on-state resistance vs. drain current (II)




Fig.6 Static drain-source on-state resistance vs. gate-source voltage




Fig.7 Static drain-source on-state resistance vs. channel temperature




Fig.8 Forward transfer admittance vs. drain current




Fig.9 Reverse drain current vs. source-drain voltage (I)

■ Typical Characteristics




Fig.10 Reverse drain current vs. source-drain voltage (II)




Fig.11 Typical capacitance vs. drain-source voltage




Fig.12 Switching characteristics (See Figures 13 and 14 for the measurement circuit and resultant waveforms)




Fig.13 Switching time measurement circuit






Fig.14 Switching time waveforms

Package Outline

SOT-23



DIMENSIONS (mm are the original dimensions)

| UNIT | A | A ₁ max. | b _p | c | D | E | e | e ₁ | H _E | L _p | Q | v | w |
|------|------------|------------------------|----------------|--------------|------------|------------|-----|----------------|----------------|----------------|--------------|-----|-----|
| mm | 1.1 0.9 | 0.1 | 0.48 0.38 | 0.15 0.09 | 3.0 2.8 | 1.4 1.2 | 1.9 | 0.95 | 2.5 2.1 | 0.45 0.15 | 0.55 0.45 | 0.2 | 0.1 |

Summary of Packing Options

| Package | Packing Description | Packing Quantity | Industry Standard |
|---------|---------------------|------------------|-------------------|
| SOT-23 | Tape/Reel, 7" reel | 3000 | EIA-481-1 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [YFW Electronics](#) manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [BUK455-60A/B](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#) [IPS70R2K0CEAKMA1](#) [SQD23N06-31L-GE3](#)
[TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [DMN1053UCP4-7](#) [SQJ469EP-T1-GE3](#) [NTE2384](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)
[IPB80P04P405ATMA2](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [NTMC083NP10M5L](#) [BXP7N65D](#) [BXP4N65F](#) [AOL1454G](#)
[WMJ80N60C4](#) [BXP2N20L](#) [BXP2N65D](#) [BXT1150N10J](#) [BXT1700P06M](#) [TSM60NB380CP](#) [ROG](#) [RQ7L055BGTGR](#) [DMNH15H110SK3-13](#)
[SLF10N65ABV2](#) [BSO203SP](#) [BSO211P](#) [IPA60R230P6](#)