


■ N-Channel MOSFET



- 1. Gate
- 2. Source
- 3. Drain


■ Features

- $V_{DS} = 100V$
- $I_D = 0.17 A$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 6 \Omega$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 10 \Omega$ ($V_{GS} = 4.5V$)
- ESD Protected 2KV HBM

■ Marking

Marking	SA
---------	----

■ Simplified outline(SOT-23)



■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current	I_D	0.17	A
Pulsed Drain Current	I_{DM}	0.68	
Power Dissipation	P_D	0.36	W
Derate Above 25°C		2.8	mW/°C
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	350	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{stg}	-55 to 150	

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =250 μA, V _{GS} =0V	100			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =100V, V _{GS} =0V			1	μA
		V _{DS} =100V, V _{GS} =0V, T _J =55°C			60	
Gate-Body Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±10	
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =1mA	0.8		2.8	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =10V, I _D =0.17A			6	Ω
		V _{GS} =10V, I _D =0.17A T _J =125°C			12	
		V _{GS} =4.5V, I _D =0.17A			10	
On State Drain Current	I _{D(ON)}	V _{GS} =10V, V _{DS} =5V	0.68			A
Forward Transconductance	g _{FS}	V _{DS} =10V, I _D =0.17A	0.08			S
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V, f=1MHz		73		pF
Output Capacitance	C _{oss}			7		
Reverse Transfer Capacitance	C _{rss}			3.4		
Gate Resistance	R _g		V _{GS} =15mV, f=1MHz		2.2	
Total Gate Charge	Q _g	V _{GS} =10V, V _{DS} =30V, I _D =0.22A		1.8	2.5	nC
Gate Source Charge	Q _{gs}			0.2		
Gate Drain Charge	Q _{gd}			0.3		
Turn-On DelayTime	t _{d(on)}	V _{DD} = 30 V, I _D = 0.28 A, V _{GS} = 10 V, R _{GEN} = 6 Ω		1.7	3.4	ns
Turn-On Rise Time	t _r			9	18	
Turn-Off DelayTime	t _{d(off)}			17	31	
Turn-Off Fall Time	t _f			2.4	5	
Body Diode Reverse Recovery Time	t _{rr}			11		
Body Diode Reverse Recovery Charge	Q _{rr}	I _F = 0.17A, di/dt= 100A/μs		3		nC
Maximum Body-Diode Continuous Current	I _S				0.17	A
Diode Forward Voltage	V _{SD}	I _S =0.34A, V _{GS} =0V			1.3	V

Note.: Pulse Test: Pulse Width ≤ 300 us, Duty Cycle ≤ 2.0%

■ Typical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

■ Typical Characteristics




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.







Figure 10. Single Pulse Maximum Power Dissipation.



Package Outline

SOT-23



DIMENSIONS (mm are the original dimensions)

UNIT	A	A ₁ max.	b _p	c	D	E	e	e ₁	H _E	L _p	Q	v	w
mm	1.1 0.9	0.1	0.48 0.38	0.15 0.09	3.0 2.8	1.4 1.2	1.9	0.95	2.5 2.1	0.45 0.15	0.55 0.45	0.2	0.1

Summary of Packing Options

Package	Packing Description	Packing Quantity	Industry Standard
SOT-23	Tape/Reel, 7" reel	3000	EIA-481-1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [YFW Electronics](#) manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [2SK2267\(Q\)](#) [BUK455-60A/B](#) [TK100A10N1,S4X\(S](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#)
[IRS2092STRPBF-EL](#) [IPS70R2K0CEAKMA1](#) [TK31J60W5,S1VQ\(O](#) [TK31J60W,S1VQ\(O](#) [TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#)
[DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [DMC2700UDMQ-7](#) [DMN2080UCB4-7](#)
[DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [IPS60R360PFD7SAKMA1](#)
[DMN2990UFB-7B](#) [SSM3K35CT,L3F](#) [IPLK60R1K0PFD7ATMA1](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [IPWS65R035CFD7AXKSA1](#)
[MCQ7328-TP](#) [SSM3J143TU,LXHF](#) [DMN12M3UCA6-7](#) [PJMF280N65E1_T0_00201](#) [PJMF380N65E1_T0_00201](#)
[PJMF280N60E1_T0_00201](#) [PJMF600N65E1_T0_00201](#) [PJMF900N65E1_T0_00201](#)