



\* CRITICAL DIMENSION

- ELECTRICAL CHARACTERISTICS
1. RATING: DC 30V 0.1A
  2. CONTACT RESISTANCE: 100mΩ MAX
  3. INSULATION RESISTANCE: 100MΩ MIN
  4. DIELECTRIC STRENGTH: AC 250V (50~60Hz)/60S
- MECHANICAL CHARACTERISTICS
1. PRACTICAL TEMPERATURE RANG: -40℃~+85℃
  2. OPERATING FORCE: 250±50gf
  3. MECHANICAL LIFE: 20,000 cycles

NO.	PART NAME	Q'TY	MATERIAL	FINISH/COLOR
7	CAM STICK	1	SUS	NATURAL
6	TERMINAL	6	BRASS STRIP	Ag COATING
5	CASE	1	PA66	GRAY
4	CONTACT	2	BRONZE	Ag CLAD
3	COVER	1	PPA	BLACK
2	SPRING	1	SUS	NATURAL
1	KNOB	1	POM	BLUE

  

X.	± 0.50	X.°	± 2°	UNITS
.X	± 0.30	.X°	± 1°	mm
.XX	± 0.10	.XX°	± 0.5°	MAT'L
.XXX	± 0.05			FINISH

OPERATION FORCE: 250GF

  

DR:	BILLY WANG 2020/08/21
CHKD:	ROC
APPD:	ROGER

  

PART NO.	YTS70L250CU
TITLE:	按钮7.0*7.0 编辑 2*3材料
DWG NO.:	YTS70L250CU

  

SCALE	1/1
SHEET	1/1
REV.	A1

**yi yu an** 深圳市怡远科技有限公司  
SHENZHEN YIYUAN TECHNOLOGY CO., LTD

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [YIYUAN](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)