


Surface Mount General Purpose Rectifier

S5A—S5M

Features

- ◆ Low profile package
- ◆ Ideal for automated placement
- ◆ Glass passivated chip junction
- ◆ High forward surge capability



Mechanical Data

Case: SMC Molded plastic body

Terminals: Plated leads solderable per MIL-STD-750,
Method 2026

High temperature soldering guaranteed: 260°C/10 seconds

Polarity: Cathode line denotes the cathode end

Mounting Position: Any

Maximum Ratings & Electrical Characteristics

Ratings at TA = 25°C unless otherwise specified

Characteristic	Symbol	S5A	S5B	S5D	S5G	S5J	S5K	S5M	Units
Peak repetitive reverse voltage	VRRM	50	100	200	400	600	800	1000	V
RMS reverse voltage	VRMS	35	70	140	280	420	560	700	V
DC blocking voltage	VDC	50	100	200	400	600	800	1000	V
Maximum average forward output current	IF(AV)	5							A
Peak forward surge current, 8.3ms single half-sine-wave, @TJ = 25°C	IFSM	150							A
Rating for fusing (t<8.3ms)	I2t	93.4							A2sec
Maximum instantaneous forward voltage @ 5A	VF	1.1							V
Maximum Reverse current Rated VR	IR	10							μA
		250							

Thermal Characteristics

Characteristic	Symbol	S5A	S5B	S5D	S5G	S5J	S5K	S5M	Units
Typical thermal resistance (Note 1)	R θJA	55							°C/W
	R θJC	15							
	R θJL	10							
Operating junction temperature range	TJ	- 55 ---- + 150							°C
Storage temperature range	TSTG	- 55 ---- + 150							°C

Note

(1) Units mounted on PCB with 10 mm x 20mmx0.1mm Copper Pads

Surface Mount General Purpose Rectifier

S5A- S5M

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)

Fig.1-Forward Current Derating Curve




Fig.2- Surge Current Derating Curve




Fig.3- Typical Forward Voltage Characteristic





Fig.4- Typical Reverse Characteristic




Surface Mount General Purpose Rectifier


S5A- S5M

Package Outline Dimensions(unit:mm)

DO-214AB (SMC)



Mounting Pad Layout(unit:mm)



Dim	Millimeters
P1	9.80
P2	6.80
P3	3.80
Q1	3.00
Q2	4.00

Ordering Information

Part No.	Marking	Package	Shipping
S5A	S5A	SMC	3000PCS /Tape&Reel
S5B	S5B	SMC	3000PCS /Tape&Reel
S5D	S5D	SMC	3000PCS /Tape&Reel
S5G	S5G	SMC	3000PCS /Tape&Reel
S5J	S5J	SMC	3000PCS /Tape&Reel
S5K	S5K	SMC	3000PCS /Tape&Reel
S5M	S5M	SMC	3000PCS /Tape&Reel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Diodes - General Purpose, Power, Switching category](#):

Click to view products by [Yjsemi manufacturer](#):

Other Similar products are found below :

[MMBD3004S-13-F](#) [RD0306T-H](#) [BAV17-TR](#) [BAV19-TR](#) [1N3611](#) [NTE156A](#) [NTE574](#) [NTE6244](#) [1SS181-TP](#) [1SS193,LF](#) [1SS400CST2RA](#)
[SDAA13](#) [SHN2D02FUTW1T1G](#) [LS4151GS08](#) [1N4449](#) [1N456A](#) [1N4934-E3/73](#) [1N914B](#) [1N914BTR](#) [1SS226-TP](#) [RFUH20TB3S](#)
[D291S45T](#) [BAV300-TR](#) [BAW56DWQ-7-F](#) [BAW75-TAP](#) [MM230L-CAA](#) [IDW40E65D1](#) [JAN1N3600](#) [LL4151-GS18](#) [053684A](#)
[SMMSD4148T3G](#) [707803H](#) [NSVDAN222T1G](#) [CDSZC01100-HF](#) [LL4150-M-08](#) [1N4454-TR](#) [BAV199E6433HTMA1](#) [BAS28-7](#)
[BAW56HDW-13](#) [BAS28 TR](#) [VS-HFA04SD60STR-M3](#) [NSVM1MA152WKT1G](#) [RGP30D-E3/73](#) [BAV99TQ-13-F](#) [BAS21DWA-7](#)
[BAV99HDW-13](#) [NTE6250](#) [NTE582-4](#) [NTE582-6](#) [MMDB30-E28X](#)