

**■ Features**

- Minature size,suitable for SMT.
- Using terminal electrode structure to restrain the parasitic component effect quite caused by lead.
- Excellent in solderability and heat resistance.
- Best frequency special property and intense ability to resist interference.
- Operating temperature:-40℃ ~ +85℃.

**■ Applications**

- Protable communication equipment and PDA,high speed electronic device.
- Used for radiation high speed noise suppression.

**■ Product Identification**



- (1) : Type
- (2) : Dimensions
- (3) : Inductance value
- (4) : Inductance Tolerance: M=±20%,K=±10%,J=±5%

**■ Shapes and Dimensions (Unit: mm)**



| TYPE     | A Max. | B Max. | C Max. | D Typ. | E Typ. | F Typ. |
|----------|--------|--------|--------|--------|--------|--------|
| YWIF2520 | 2.92   | 2.23   | 2.70   | 1.27   | 1.02   | 2.54   |

### ■ YWIF2520 Series

| Part Number   | L (uH)   | Freq. (MHz) | Q Typ. | SRF Min. (MHz) | Rdc Max. ( $\Omega$ ) | Isat Max. (mA) |
|---------------|----------|-------------|--------|----------------|-----------------------|----------------|
| YWIF2520-R39K | 0.39±10% | 7.9         | 12     | 400            | 0.40                  | 500            |
| YWIF2520-R47K | 0.47±10% | 25          | 12     | 600            | 0.27                  | 700            |
| YWIF2520-R56K | 0.56±10% | 7.9         | 12     | 230            | 0.62                  | 700            |
| YWIF2520-R68K | 0.68±10% | 7.9         | 12     | 230            | 0.62                  | 700            |
| YWIF2520-R82K | 0.82±10% | 7.9         | 12     | 230            | 0.62                  | 700            |
| YWIF2520-R90K | 0.90±10% | 7.9         | 20     | 300            | 0.35                  | 1400           |
| YWIF2520-1R0K | 1.0±10%  | 7.9         | 18     | 230            | 0.62                  | 700            |
| YWIF2520-1R2K | 1.2±10%  | 7.9         | 18     | 210            | 0.68                  | 650            |
| YWIF2520-1R5K | 1.5±10%  | 7.9         | 18     | 190            | 0.76                  | 630            |
| YWIF2520-1R8K | 1.8±10%  | 7.9         | 18     | 170            | 0.84                  | 600            |
| YWIF2520-2R0K | 2.0±10%  | 7.9         | 18     | 160            | 1.10                  | 550            |
| YWIF2520-2R2K | 2.2±10%  | 7.9         | 18     | 150            | 1.10                  | 520            |
| YWIF2520-2R7K | 2.7±10%  | 7.9         | 18     | 135            | 1.28                  | 490            |
| YWIF2520-3R3K | 3.3±10%  | 7.9         | 18     | 120            | 1.46                  | 450            |
| YWIF2520-3R9K | 3.9±10%  | 7.9         | 18     | 105            | 2.30                  | 300            |
| YWIF2520-4R7K | 4.7±10%  | 7.9         | 18     | 90             | 2.00                  | 400            |
| YWIF2520-5R6K | 5.6±10%  | 7.9         | 15     | 80             | 1.80                  | 380            |
| YWIF2520-6R8K | 6.8±10%  | 7.9         | 15     | 70             | 2.00                  | 360            |
| YWIF2520-8R2K | 8.2±10%  | 7.9         | 15     | 65             | 2.65                  | 330            |
| YWIF2520-100K | 10±10%   | 2.5         | 12     | 60             | 2.95                  | 300            |
| YWIF2520-150K | 15±10%   | 2.5         | 12     | 30             | 3.70                  | 280            |
| YWIF2520-180K | 18±10%   | 2.5         | 12     | 26             | 4.00                  | 160            |
| YWIF2520-220K | 22±10%   | 2.5         | 12     | 22             | 6.14                  | 270            |
| YWIF2520-330K | 33±10%   | 2.5         | 10     | 12             | 7.00                  | 200            |

## ■ YWIF2520 Series

| Part Number   | L (uH)  | Freq.<br>(MHz) | Q<br>Min. | SRF Min.<br>(MHz) | Rdc Max.<br>(Ω) | Isat Max.<br>(mA) |
|---------------|---------|----------------|-----------|-------------------|-----------------|-------------------|
| YWIF2520-390K | 39±10%  | 2.5            | 10        | 16                | 10.00           | 180               |
| YWIF2520-470K | 47±10%  | 2.5            | 10        | 10                | 10.70           | 160               |
| YWIF2520-560K | 56±10%  | 2.5            | 10        | 8                 | 12.00           | 170               |
| YWIF2520-680K | 68±10%  | 2.5            | 10        | 6                 | 13.50           | 145               |
| YWIF2520-820K | 82±10%  | 2.5            | 8         | 6                 | 20.00           | 100               |
| YWIF2520-101K | 100±10% | 1              | 8         | 4                 | 21.00           | 80                |

- ※ Rating DC current:temperature rise( $\Delta T$ ) is 40 °C approximately at Irms.
- ※ Saturation DC current:Inductance drop approximately 30% of L0 at Isat.
- ※ Storage temp.: -10°C ~ + 40°C R.H.:65% Max.
- ※ Moisture sensitivity level(MSL)2(1 year floor life at<30°C/65% relative humidity).


**■ Soldering Conditions**

**Figure 1.  
Re-flow  
Soldering  
(Lead Free)**



- Note:
- Preheat circuit and products to 150°C
  - 260°C tip temperature (max)
  - Reflow times: no more than 2 times
  - Solder paste thickness: the best 0.08mm is ,but max is 0.1mm

**Figure 2.  
Hand  
Soldering**




- Note:
- Use a 20 watt soldering iron with tip diameter of 1.0mm
  - Limit soldering time to 3 sec.

**■ Taping Dimensions(Unit:mm)**




| TYPE     | W    | A    | B    | D    | P    | K Max | T Max | MPQ  |
|----------|------|------|------|------|------|-------|-------|------|
| YWIF2520 | 8.00 | 1.50 | 2.30 | 3.50 | 4.00 | 1.10  | 0.30  | 2000 |

**■ Reel Dimensions(Unit:mm)**




| TYPE     | W       | W1        | A        | B        | C        | D      |
|----------|---------|-----------|----------|----------|----------|--------|
| YWIF2520 | 178±2.0 | 8.40±1.50 | 4.3±0.20 | 5.0±0.10 | 3.0±0.10 | 58±2.0 |

**Leader and Blank portion**



1. Missing chips number within 0.1% of the number per reel or 1pcs, whichever is greater, and are not continuous.
2. The top tape and bottom tape shall not protrude beyond the edges of the tape and shall not cover sprocket hole.
3. Cumulative tolerance of sprocket holes, 10 pitches:  $\pm 0.3\text{mm}$ .
4. Peeling off force: 10gf to 100gf in the direction show below for 8mm carrier tapes and 10gf to 130gf for 12mm to 56mm wide carrier tapes.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fixed Inductors](#) category:*

*Click to view products by [YJYCOIN](#) manufacturer:*

Other Similar products are found below :

[CR32NP-100KC](#) [70F224AI](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#)  
[PE-53601NL](#) [PE-53602NL](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2-R47-R](#) [HC8-1R2-R](#)  
[HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-4R7M](#) [RCP1317NP-391L](#) [DH2280-4R7M](#) [DS1608C-106](#) [B10TJ](#) [B82498B3101J000](#) [ELJ-](#)  
[RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#) [1812LS-104XJ](#) [1812LS-105XJ](#) [1812LS-124XJ](#) [1812LS-154XJ](#) [1812LS-223XJ](#)  
[1812LS-224XJ](#) [1812LS-563XJ](#) [1812LS-683XJ](#) [1812LS-824XJ](#) [NIN-FB101JTR110F](#) [NIN-FB471JTR62F](#) [NIN-FC1R5JTR220F](#) [NIN-](#)  
[HCR15JTRF](#) [NIN-HCR33JTRF](#) [NIN-HDR22JTRF](#) [NIN-HDR82JTRF](#) [NIN-HK2N7STRF](#) [NIN-PA150KTR370F](#) [NIN-PB100KTR550F](#)