



Electrical Characteristics:
 Current rating: 0.5A AC/DC
 Voltage rating: 100V AC/DC
 Temperature range: -25°C~+85°C
 Withstand Voltage: 200V AC/Minute
 Contact Resistance: ≤ 20mΩ
 Insulation resistance: ≥ 500mΩ
 Relative Humidity: 93%+40°C

Material Description:
 Terminal: Phosphor Bronze Tin-plated
 Fitting Nail: Brass Tin-plated
 Housing: Thermoplastic(UL94V-0)
 Slider: Thermoplastic(UL94V-0)

PIN#	DIM=A	DIM=B	DIM=C	DIM=D	DIM=E
4P	7.6	6.5	1.50	2.6	
5P	8.1	7.0	2.00	3.1	
6P	8.6	7.5	2.5	3.6	
7P	9.1	8.0	3.0	4.1	
8P	9.6	8.5	3.5	4.6	
9P	10.1	9.0	4.0	5.1	
10P	10.6	9.5	4.5	5.6	
11P	11.1	10.0	5.0	6.1	
12P	11.6	10.5	5.5	6.6	
13P	12.1	11.0	6.0	7.1	
14P	12.6	11.5	6.5	7.6	
15P	13.1	12.0	7.0	8.1	
16P	13.6	12.5	7.5	8.6	
17P	14.1	13.0	8.0	9.1	
18P	14.6	13.5	8.5	9.6	
19P	15.1	14.0	9.0	10.1	
20P	15.6	14.5	9.5	10.6	
21P	16.1	15.0	10.0	11.1	
22P	16.6	15.5	10.5	11.6	
23P	17.1	16.0	11.0	12.1	
24P	17.6	16.5	11.5	12.6	
25P	18.1	17.0	12.0	13.1	
26P	18.6	17.5	12.5	13.6	
27P	19.1	18.0	13.0	14.1	
28P	19.6	18.5	13.5	14.6	
29P	20.1	19.0	14.0	15.1	
30P	20.6	19.5	14.5	15.6	
31P	21.1	20.0	15.0	16.1	
32P	21.6	20.5	15.5	16.6	
33P	22.1	21.0	16.0	17.1	
34P	22.6	21.5	16.5	17.6	
35P	23.1	22.0	17.0	18.1	
36P	23.6	22.5	17.5	18.6	
37P	24.1	23.0	18.0	19.1	
38P	24.6	23.5	18.5	19.6	
39P	25.1	24.0	19.0	20.1	
40P	25.6	24.5	19.5	20.6	
41P	26.1	25.0	20.0	21.1	
42P	26.6	25.5	20.5	21.6	
43P	27.1	26.0	21.0	22.1	
44P	27.6	26.5	21.5	22.6	
45P	28.1	27.0	22.0	23.1	
46P	28.6	27.5	22.5	23.6	
47P	29.1	28.0	23.0	24.1	
48P	29.6	28.5	23.5	24.6	
49P	30.1	29.0	24.0	25.1	
50P	30.6	29.5	24.5	25.6	
51P	31.1	30.0	25.0	26.1	
52P	31.6	30.5	25.5	26.6	
53P	32.1	31.0	26.0	27.1	
54P	32.6	31.5	26.5	27.6	
55P	33.1	32.0	27.0	28.1	
56P	33.6	32.5	27.5	28.6	
57P	34.1	33.0	28.0	29.1	
58P	34.6	33.5	28.5	29.6	
59P	35.1	34.0	29.0	30.1	

ROHS2.0

本圖紙知識產權及版權由深圳市永丰盈电子有限公司所有,未經書面許可不准擅自傳閱、复制和修改。本公司保留法律追究的权利。	类别	FPC	品名	CS-1191U-12	X.	±0.50	材料		单位	mm	SHEET 1 OF 1	
	版本	A/0	设计	李文畅	X.X	±0.40	颜色		比例	1:1	修改内容	修改日期
	制定部门	工程部	绘制	李文畅	X.XX	±0.30	画法		数量			
	工程图号	CST-1191U	审核	姚培柱	X.XXX	±0.20	CST 深圳市永丰盈电子有限公司 ShenZhenYongFengYing ELEECTRONICS CO.,LTD.					
	制定日期	2018/05/07	核准	周中湖	X.XXXX	±0.10						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC & FPC Connectors](#) category:

Click to view products by [Yongfengying Electronics](#) manufacturer:

Other Similar products are found below :

[00-6200-227-022-800](#) [006205250500825+](#) [006205280500825+](#) [FPH-1602G](#) [086222026001800](#) [52610-0675](#) [62674-201121DLF](#) [52746-1671-TR250](#) [10051922-1610EHLF](#) [10051922-2810EHLF](#) [686322124422](#) [XF3M-2915-1B-R100](#) [AYF353125A](#) [AYF530665TA](#) [AYF534065TA](#) [20FLH-RSM1-TB](#) [207356-1](#) [SFW12R-5STE9LF](#) [SFW18R-1STAE9LF](#) [SFW4R-5STE9LF](#) [52807-0430](#) [046283021002868+](#) [FFC05011-10SBB114W5M](#) [502250-8027](#) [67000-008LF](#) [200528-0260](#) [FH28K-10S-0.5SH](#) [FH52K-6S-0.5SH](#) [0.5K-DX-30PWB](#) [DS1020-08-10VBT12](#) [THD0515-34CL-GF](#) [X05A10L28G](#) [ECC2841061EU](#) [1.0K-DHQX-16PWB](#) [1.0K-DHQX-30PWB](#) [1775333-6](#) [10054365-202110ELF](#) [10054365-242110ELF](#) [10054365-282110ELF](#) [10064555-392220HLF](#) [59453-041110EBHLF](#) [59453-091110EDHLF](#) [62674-241141ALF](#) [62684-432100ALF](#) [62684-451100AHLF](#) [62684-5721N0ALF](#) [HFW11R-1STE1MTLF](#) [HFW12R-1STE9LF](#) [HFW14R-1STE9MTLF](#) [HFW18S-2STE9LF](#)