



MMBTA92

TRANSI STOR (PNP)

MARKING:



Equivalent Circuit:



SOT-23



FEATURES:

- ※ High Breakdown Voltage

MAXIMUM RATINGS (Ta=25°C unless otherwise noted)









Parameter	Symbol	Value	Unit
Collector-Base Voltage	VCBO	-300	V
Collector-Emitter Voltage	VCEO	-300	V
Emitter-Base Voltage	VEBO	-5	V
Collector Current -Continuous	IC	-200	mA
Collector Current -Pulsed	ICM	-500	mA
Collector Power Dissipation	PC	300	mW
Thermal Resistance From Junction To Ambient	R _{θJA}	417	°C/W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55~+150	°C


ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Collector-base breakdown voltage	V(BR)CBO	IC= -100µA, IE=0	-300			V
Collector-emitter breakdown voltage	V(BR)CEO	IC= -1mA, IB=0	-300			V
Emitter-base breakdown voltage	V(BR)EBO	IE=-100µA, IC=0	-5			V
Collector cut-off current	ICBO	VCB=-120 V , IE=0			-0.25	µA
Collector cut-off current	ICEO	VCB=-150V , IE=0			-5	µA
Emitter cut-off current	IEBO	VEB= -4V , IC=0			-0.1	µA
DC current gain	hFE	VCE=-5V, IC= -1mA	80			
	hFE	VCE=-5V, IC= -10mA	100		200	
	hFE	VCE=-5V, IC= -50mA	50			
Collector-emitter saturation voltage	VCE(sat)	IC=-50 mA, IB= -5mA			-2	V
Base-emitter saturation voltage	VBE(sat)	IC=-50 mA, IB= -5mA			-1	V
Transition frequency	fT	VCE=-20V, IC= -10mA f=300MHz	50			MHz

CLASSIFICATION OF hFE

Rank	L	H	J
Range	80-100	100-200	200-250

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS


SOT-23 PACKAGE OUTLINE DIMENSIONS


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
theta	0°	8°	0°	8°

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Bipolar Transistors - BJT category:

Click to view products by Yongytai Electronics manufacturer:

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MMBT-2369-TR](#) [BC546/116](#) [BC557/116](#) [BSW67A](#) [NJVMJD148T4G](#) [NTE123AP-10](#) [NTE153MCP](#) [NTE16](#)
[NTE195A](#) [NTE92](#) [2N4401-A](#) [2N6728](#) [2SA1419T-TD-H](#) [2SA2126-E](#) [2SB1204S-TL-E](#) [2SC2712S-GR,LF](#) [SP000011176](#) [2N2907A](#) [2N3904-NS](#) [2N5769](#) [2SC2412KT146S](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [MJE340](#) [Jantx2N5416](#) [US6T6TR](#) [NJL0281DG](#) [732314D](#) [CPH3121-TL-E](#)
[CPH6021-TL-H](#) [873787E](#) [IMZ2AT108](#) [MMST8098T146](#) [UMX21NTR](#) [MCH6102-TL-E](#) [NJL0302DG](#) [30A02MH-TL-E](#) [NTE13](#) [NTE26](#)
[NTE282](#) [NTE323](#) [NTE350](#) [NTE81](#) [STX83003-AP](#) [JANTX2N2920L](#) [JANSR2N2222AUB](#) [CMLT3946EG TR](#) [2SA1371D-AE](#)