



Circuit Diagram



凸柄 Convex handle



短柄 Short handle


Number of digits (位数)	1P	2P	3P	4P	5P	6P	7P	8P	9P	10P	12P
Cover/black 凸柄	TO-01	TO-02	TO-03	TO-04	TO-05	TO-06	TO-07	TO-08	TO-09	TO-10	TO-12
Short handle 短柄	TO-01D	TO-02D	TO-03D	TO-04D	TO-05D	TO-06D	TO-07D	TO-08D	TO-09D	TO-10D	TO-12D

NO.	Name	Number	Qty	Material	Remarks
Ⓐ	Base	/	1	PPS	Black
Ⓑ	Cover	/	1	PPS	Black
Ⓒ	Handle	/	2	PA46	White
Ⓓ	Shrapnel	/	2	Beryllium copper	Gold plating
Ⓔ	Terminal	/	4	Brass	Gold plating

design	date	name	model	TO-02
Review	date			
Approved	date			
Drawing number:				
Proportion 1:1	unit	mm	gate number	

NOTE:
 1. Rating: 24V 25mA DC
 2. Insulation Resistance: $\geq 100 \text{ M}\Omega$
 3. Withstand voltage: AC 500V 1Minute
 4. Operating Force Range: 500gf Max
 5. Mechanical Life: 3,000 Cycles

PCB Layout (Pattern Side)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIP Switches/SIP Switches](#) category:

Click to view products by [Yuandi](#) manufacturer:

Other Similar products are found below :

[78M03S](#) [79B10T](#) [8136-475G4T](#) [G7G-1A2-CB-DC12](#) [A7SS-M](#) [DBP 2110](#) [DBP 2112](#) [DBS1008](#) [DHN02FTVTR](#) [DHN10T](#) [DHS108](#) [DM-08](#)
[DP-10-H](#) [DPL08TN](#) [DRD16CSE04](#) [DRR4010](#) [DRR60016](#) [DRS4016](#) [BD06E](#) [1825008-1](#) [1825444-1](#) [218-8LPSTF](#) [219-6LPSTRF](#)
[25.350.0653.0](#) [LA2-DC12](#) [SBS 5004 TG](#) [SDA10H1BDA](#) [97R06ST](#) [A2C-2A5](#) [1825444-7](#) [ADE08SA04](#) [ADE12S04](#) [2-1825058-8](#) [CCVA](#)
[2.5/ 4-G-5.08 P26THRR32](#) [25.330.0653.1](#) [25.352.0353.0](#) [MDG305ST](#) [IKN0600000](#) [IKN0800000](#) [LA2-002-DC24](#) [DBP2008](#) [DBS1003](#)
[DBS2008](#) [438872000](#) [WT11-D1-06](#) [DM-02](#) [DRD10CRAE04](#) [DRS1604](#) [DSR02T](#) [DSS 208 N](#)