

零件承认书

客户名称: _____

客户料号: _____

规格描述: **T9*5*3MM 0.35MM*2P*10.5TS L=35-100UH**

增益料号: **C07-0300-00149-00297**

日期: **2016/8/15**

版本: **A**

增益签核:

制订	审核	核准
张翔	刘业明	柯文学

客户签核:

工程	审核	核准



东莞市增益实业有限公司

地址: 东莞市清溪镇三星路1号

电话: 0769-87321000

传真: 0769-87891229

物料类型:

环形电感

日期:

2016/8/15


版本:

A

外观尺寸

客户料号:		增益料号:	0
规格描述:	T9*5*3MM 0.35MM*2P*10.5TS L=35-100UH		


1. 尺寸图 (单位: MM)



DIM	A	B	L	P	P1			
mm	12.0	6.0	5.0	5.0	5.0			
SPEC	MAX	MAX	±1.0	±1.0	±1.0			

- 注意:
- 1 绕线平整无交叉、无打结。
 - 2 本体无异物。

2. 绕线结构



绕组	起点	终点	材料	圈数	备注
N1	1	3	漆包线0.35MM	10.5ts REF	
N2	4	6	三层绝缘线0.35MM	10.5ts REF	



地址：东莞市清溪镇三星路1号

电话：0769-87321000

传真：0769-87891229

物料尖空：

环形电感

日期：

2016/8/15

版本：

A

制订	张翔	审核	刘业明	核准	柯文学
----	----	----	-----	----	-----

电气性能


客户料号:		增益料号:	0
规格描述:	T9*5*3MM 0.35MM*2P*10.5TS L=35-100UH		

3. 电气特性 (室内温度 25℃ 室内湿度 65±5% RH)

TEST ITEM (测试项目)	TEST CONDITION (测试条件)	TEST WINDING (测试绕组)	RESULT (条件范围)
电感 测试仪器: HP-4284A	1KHZ/0.25V	1~3 6~4	35-100UH
Q值 测试仪器: HP-4284A	1KHZ/0.25V	1~3 6~4	
DCR (电阻) 测试仪器: HK-502BC	AT25℃	1~3 6~4	
HI-POT TEST (耐压测试) 测试仪器: HY-7110			

4. 原材料清单

NO	材料	规格	厂家	安规编号
1	磁芯	T9*5*3	ZEE	
2	铜线	2UEW	TAI-I	E201757
3				
4				
5				
6				

	东莞市增益实业有限公司 地址: 东莞市清溪镇三星路1号 电话: 0769-87321000 传真: 0769-87891229			物料类型:	环形电感
				日期:	2016/8/15
				版本:	A
制订	张翔	审核	刘业明	核准	柯文学

测试报告

客户料号:						增益料号:		0					
规格描述:		T9*5*3MM 0.35MM*2P*10.5TS L=35-100UH											
交货数量	抽样数	抽样基准 MIL-STD-105E <input checked="" type="checkbox"/> 正常 检验标准 <input type="checkbox"/> 加严 <input type="checkbox"/> 减严		判定标准		测试环境		分项检查判定					
				主要	次要	温度	湿度	尺寸	外观	特性			
5PCS	5PCS			0.1	0.4	25℃	65%		OK		OK		OK
绝缘电阻DC	COIL TO CORE	V	COIL TO COIL	V	测试仪器		<input type="checkbox"/> CH-9053	<input checked="" type="checkbox"/> HK-502BC					
		MΩ		MΩ	<input checked="" type="checkbox"/> HP-4284A	<input type="checkbox"/> CH-100	<input type="checkbox"/> HY-7110						
耐电压AC	SEC	SEC		<input type="checkbox"/> HP-42841A	<input type="checkbox"/> CH-1320	<input checked="" type="checkbox"/> HK-310							
	KV	KV		<input type="checkbox"/> TF-6815	<input type="checkbox"/> HK-1062	<input checked="" type="checkbox"/> 卡尺							
测试条件	1KHZ/0.25V				外观尺寸 (mm)								
PIN	L(S-F)		DCR(S-F)		A	B	C	D	E	F	G		
SPEC	35-100UH												
±			MAX										
1	45.0												
2	48.0												
3	50.0												
4	51.0												
5	60.0												
6													
7													
8													
9													
10													
X													
R													
备注:													
 东莞市增益实业有限公司 地址: 东莞市清溪镇三星路1号 电话: 0769-87321000 传真: 0769-87891229						物料类型:		环形电感					
						日期:		2016/8/15					
						版本:		A					
制订	张翔		审核	刘业明		核准	柯文学						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [Zeng Yi](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)