

Mini Industrial Keyboard G86-52400 Series



Enhanced 83 Key Layout, Offers an IP54 for Spill and Dust Resistant for Harsh Environments.

Facts & Features

- Reduced-size keyboard with QWERTY layout
- Enhanced US 83-Position Key Layout
- Robust Product Design with IP 54 Spill and Dust Resistant Key Field for Harsh Environments
- Plug & Play Configuration for all Common POS Features
- Yellow Status LEDs for Improved Visibility in Rooms with Artificial Illumination

Compatibility

- Designed for MS Windows™ XP
- Windows™ 2000, XPembedded, Vista
- Works with Linux, Mac, UNIX, Sun

Agency Approvals

- cUrus, FCC, CE, BSMI, VCCI, C-Tick, WHQL VDE, WEEE, RoHS

Technical Data

- Interface:
USB 2.0
- Cable Length:
Approx. 1.85 m
- Layout:
Compact size 83 position US key Layout
- Weight:
Net: 936 g
With Packaging 1,217g
- Dimensions:
Keyboard: 11.8" x 6.3" x 1"
Packaging: 13.5" x 8.5" x 1.75"
- Current Input:
typ. 35 mA
- Keyswitch Lifetime:
25 million operations
- Operating Temperature:
0°C to +50°C
- Storage/Transport Temperature:
-20°C to +60°C
- Packaging Unit:
21 keyboards per master carton
12 master cartons per pallet (252 pcs.)
- Warranty:
2 years

Order Description

Service Design	Order Number	Interface	Color
Heavy Use	G86-52400EUADAA	USB	black

Other country versions upon request.

Cherry Americas, LLC
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6508
Internet: www.cherryamericas.com

E-Mail: keyboardsupport@cherryamericas.com

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

Rev Date: January 17, 2017

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Input Devices](#) category:

Click to view products by [ZF Cherry](#) manufacturer:

Other Similar products are found below :

[80260-00](#) [81485-28](#) [81521-08](#) [FKB4720-103](#) [84250-26](#) [84980-04](#) [84S-AC1-000](#) [JD-0700EU-2](#) [JM-0800-2](#) [JW-T0100](#) [89498-13](#) [89758-05](#)
[89886-26](#) [89941-00](#) [G80-3000LSCEU-2](#) [MJ0FGGRY](#) [JM-0800-0](#) [84S-BB1-004](#) [81601-26](#) [UL21KMZQ](#) [G8011900LPMUS0](#) [G84-](#)
[4700LUCUS-0](#) [81485-26](#) [84105-13](#) [V400-W24 5M](#) [V400-W23 5M](#) [G84-5200LCMEU-2](#) [DT2257X20V00GRY](#) [84Z2029-78](#) [84Z2029-79](#)
[V400-W23P 5M](#) [VW3A8151R20U](#) [V400-W24 15M](#) [LT1332D](#) [V400-W24 10M](#) [V400-W24P 15M](#) [V400-WM0 1M](#) [V400-W24P 10M](#) [V400-](#)
[W23P 10M](#) [TCS-1492OP](#) [V400-W23 3M](#) [LT1372D](#) [LP1007EXXH00R](#) [DT2253X20V00BLK](#) [100133BX](#) [EZ08-230013](#) [81248-04](#) [89887-26](#)
[90215-00](#) [HB110C3NWBNA](#)