

CHERRY MX1A-Cxxx



Models may vary from the image shown

The Original: Key module with CHERRY Gold Crosspoint technology

Clear switch: With tactile pressure point.

Original CHERRY MX is the world's leading precision technology for mechanical key modules. The CHERRY Gold Crosspoint contact concept and the unprecedented production quality "made in Germany" are unique. MX inside ensures unrivalled quality, precision and reliability.

Key benefits

- Clear switch: With tactile pressure point
- Mechanical high-precision key module
- In use worldwide for Original CHERRY keyboards and in keyboards of demanding input device manufacturers
- Safe and long-lasting reliability of switching performance and characteristics
- · Short bounce time for high switching frequency (such as for fast typing)
- · Self-cleaning contacts, resistant to dust and dirt
- Over 50 million keystrokes / contact switches per module with no loss of quality
- Proven a billion times over and continuously developed
- World exclusive CHERRY Gold Crosspoint technology


Technical Data:

Keymodule:

 Switch type: MX • Protection class: IP40

• Operation characteristics: CLEAR SWITCH Pressure point

(65cN)



Fastening: Product dependant, see table "Models"

Switching voltage: 12 V AC/DC max.

Switching current: 10 mA AC/DC max.

• Dielectric strength: 500 V / 50Hz

• Durability: > 50 million actuations

Contact configuration: Single-pole contact

• Actuator travel: 4 - 0.5 mm

Pretravel: 2 ± 0.6 mm

 Initial force: 40 ± 15 cN Actuation force: 55 ± 20 cN

• Pressure point force: 65 ± 20 cN

• Bounce time: < 5 ms (during actuation with 0,4 m/s)

• Standard lead spacing: 19.05 mm (16 mm min.)

• Lighting: Product dependant, see table "Models"

• Decoupling diode: Product dependant, see table "Models"

• Wire jumper: Product dependant, see table "Models"

• Insulation materials: Thermoplastics (min.UL 94 HB)

Spring: Stainless steel

Contacts: High-quality gold alloy

Storage Temperature: 5°C to 40°C

Operating Temperature: -40°C to 70°C

• Humidity: Storage: average <50% max. 3 months / 75% max.

15 days, operation: 5% to 95% without condensation

For detailed information and the layout of the details described above, please do not hesitate to ask for our technical specifi cations and drawing.

Warranty:

2 years



Errors, technical changes and delivery possibilities excepted. Technical information refers only to the specifications of the products. Features may differ from the information provided.



Models:

	Product name	Order number	Fastening	Lighting	Decoupling diode	Wire jumper
1	CHERRY MX1A-Cxxx	MX1A-C1DN	Snap fastening in frame	no	yes	no
2	CHERRY MX1A-Cxxx	MX1A-C1DW	Fixing pins in the printed circuit board	no	yes	no
3	CHERRY MX1A-Cxxx	MX1A-C1GN	Snap fastening in frame	LED in green	no	no
4	CHERRY MX1A-Cxxx	MX1A-C1GW	Fixing pins in the printed circuit board	LED in green	no	no
5	CHERRY MX1A-Cxxx	MX1A-C1JW	Fixing pins in the printed circuit board	no	no	yes
6	CHERRY MX1A-Cxxx	MX1A-C1NN	Snap fastening in frame	no	no	no
7	CHERRY MX1A-Cxxx	MX1A-C1NW	Fixing pins in the printed circuit board	no	no	no
8	CHERRY MX1A-Cxxx	MX1A-C1RW	Fixing pins in the printed circuit board	LED in red	no	no

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by ZF Cherry manufacturer:

Other Similar products are found below:

8940K2012 LW1L-M1C10V-A LW1L-M1C70-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M22-D-R-GB0/K11 M7E-HRN2 67021K512 67081K512X 701PB580 7199K101 810K12910 810KSV30B MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911 8646AB6X718UL 8646ABUL 9001KXRK 907AYY100 PMHD155A1 9533CD4+U574+U4922 95-414.000 99-450.837 99-453.837 PV3H2B0NN-341 1203MRA A22NZBGANGA A22NZBNANGA A22NZMPATRA A2PMA1X03EC56 A3A-5123-02 A3A-7140 A3A-7340 A3U-TMW-A2C-5M A595 12037A2ULCSA ABD122N-B 1211390004