

CHERRY SmartTerminal ST-1144



Models may vary from the image shown

USB Smart Card Reader

Smart, stable and can be operated with one hand. The SmartTerminal ST 1144 reads and writes your chipcards - and with extremely low power consumption to boot. Whether access controls, network logon or smart card-based Internet transactions - the SmartTerminal with USB connection supports you in protecting your sensitive data in an easy and reliable way.

Key Benefits

- High-quality USB-smartcard reader
- OmniKey 3121 (Aviator) compatible
- USB 2.0-compatible
- Weighted base for "single-handed operation"
- PC/SC smartcard reader
- Protocols: T=0, T=1, S=8, S=9, S=10
- CCID compatible
- EMVco Level 1 compliant
- CAC and FIPS 201 compliant
- TAA compliant

Technical Data:

Housing Color:

light grey/black

Weight (product):

approx. 300 g / 10.58 oz

Total Weight (with packaging):

approx. 350 g / approx. 12.35 oz

Cable Length:

approx. 1.75 m / approx. 5.74 ft

Storage Temperature:

-20°C to 50°C / -4° F to 122° F

Operating Temperature:

0°C to 60°C / 32° F to 140° F






Current Consumption:

max. 100 mA

Interface:

- USB

Product Approvals:

- cURus 
- VDE GS 
- VCCI 
- CE 
- FCC 
- VDE 

System Requirements:

- USB connection

Box Contents:

- CHERRY SmartTerminal ST-1144
- Operating instructions in hard copy

Dimensions (product):

approx. 75 x 51 x 55 mm / approx. 2.95 x 2.01 x 2.17 in

Packaging Dimensions:

approx. 117 x 59 x 147 mm / approx. 4.61 x 2.32 x 5.79 in

Packaging (version):

White box

Smart card reader:

- Hardware Interface: USB
- Chip-card Protocols: T=0, T=1, S=8, S=9, S=10
- Contact: mechanical swipe reader
- Software Interface: CT-API, PC/SC, CCID
- Mating Cycles: approx. 100,000 operations
- Compatible Chip Card Types: Reads and writes on all ISO 7816 cards
- Transmission Speed Reader <==> Card: 412,903 Bit/s
- Transmission Speed Reader <==> System: max. 12 MBit/s
- Chip Card Pulse Frequency: 4.8 MHz

Packaging Unit:

- Number of products in the master package: 10
- Number of master packages per pallet: 54

Warranty:

2 years

Errors, technical changes and delivery delays may occur.
Technical information refers only to the specifications of the
products. Features may differ from the information provided.

Models:

(possible country/layout versions, others available on request)

	Product Name	Order Number
1	CHERRY SmartTerminal ST-1144	ST-1144UB

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modules Accessories](#) category:

Click to view products by [ZF Cherry](#) manufacturer:

Other Similar products are found below :

[7010-0001](#) [AX98219](#) [A1UL8RISER](#) [F1UJPMICRISER](#) [FHW1U16RISER](#) [20-101-0440](#) [MBCDROM](#) [AX61221TM](#) [VM-105](#) [EA](#)
[CARREDIPTFT02](#) [RK-210E-B](#) [E226171106](#) [88606200030E](#) [SI-HDMI-EDID-EM](#) [MIC-75M13-00A1E](#) [FPM-1000T-SMKE](#) [AMK-R004E](#)
[96FMCF-ST2ADAPTER1](#) [AHWKPTP12GBGB](#) [AXXSTCPUCAR](#) [FPK-07-R10](#) [Mini Din 6P to 6P HARNESS](#) [FPF1320 POWER](#)
[MULTIPLEXER CARRIER](#) [881261510A0E](#) [AXXP3SWX08080](#) [conga-B7XD/CSP-Cu-B](#) [881281021A0E](#) [HFT for mounting KIT](#)
[FN928X_FN929X](#) [BB-MH112-1A](#) [15100600](#) [9-5000-1116](#) [BKCMCR1ABB](#) [70763](#) [98R3612003E](#) [881261910A0E](#) [106897](#) [48222R](#)
[BREAK OUT BOARD 20](#) [4D ARDUINO ADAPTOR SHIELD II](#) [20926110901](#) [PYCASE GREEN](#) [PYCASE BLUE](#) [FP15072_ZORYA-SC-](#)
[HEKLA](#) [20952000004](#) [20953000007](#) [DP-DVI-R10](#) [575-BBIS](#) [RACK-220GW/A130B](#) [492-BBKM](#) [IP411](#)